

SLN-1103E

SLN-1203E

1 or 2 Lines  
SIP Phone



- 1 or 2 lines SIP phone.
- 3 customizable service dials.
- Dual Ethernet Ports.
- Message waiting indicator.
- Faceplate with customizable hotel logo.

**AEi** brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



## 1. Features

	Keys	1203E	1103E
	<ul style="list-style-type: none"> <li>Dial keys (0~9, *, #)</li> <li>Line keys Line1, Line2 with LED, End</li> <li>Function keys Hold, Redial, Volume up/down, 3 Service dial keys</li> </ul>	<ul style="list-style-type: none"> <li>Dial keys (0~9, *, #)</li> <li>Line keys Line1, Line2 with LED, End</li> <li>Function keys Hold, Redial, Volume up/down, 3 Service dial keys</li> </ul>	<ul style="list-style-type: none"> <li>(0~9, *, #)</li> <li>N/A</li> <li>Hold, Redial, Volume up/down, 3 Service dial keys</li> </ul>
Phone Features	<ul style="list-style-type: none"> <li>One or Two Lines</li> <li>3 programmable service dial keys</li> <li>Red color message waiting indicator for ringing and message waiting</li> </ul>	<ul style="list-style-type: none"> <li>Handset and ringer volume control</li> <li>Redial last call</li> <li>Call Hold and resume</li> <li>Dual Ethernet Ports</li> <li>Firmware upgrade via web.</li> </ul>	
Easy Administration	<ul style="list-style-type: none"> <li>Web GUI.</li> <li>Auto provisioning</li> </ul>		
Codec	<ul style="list-style-type: none"> <li>G.711</li> </ul>		
Network Protocol	<ul style="list-style-type: none"> <li>Static IP, DHCP Client</li> <li>HTTP server</li> </ul>	<ul style="list-style-type: none"> <li>ToS / VLAN IEEE 802.1 p/q</li> <li>STUN (RFC 3489)</li> </ul>	
SIP	<ul style="list-style-type: none"> <li>SIP V2 (RFC3261)</li> </ul>		
Security	<ul style="list-style-type: none"> <li>Web login authentication for web setup</li> </ul>	<ul style="list-style-type: none"> <li>MD5 for SIP authentication (RFC2069/ RFC2617)</li> </ul>	
DTMF	<ul style="list-style-type: none"> <li>In-Band / Out-of-Band DTMF(RFC2833) / SIP Info (RFC2976)</li> </ul>		
Voice Quality	<ul style="list-style-type: none"> <li>CNG: Comfortable noise generator.</li> <li>LEC: Line Echo Canceller.</li> <li>Jitter buffer.</li> </ul>		
Tones	<ul style="list-style-type: none"> <li>Ring back tone (local), Busy tone, Dial tone</li> </ul>		

## 2. Hardware Specifications

LED Indications	<ul style="list-style-type: none"> <li>Line keys and Message waiting indicator</li> </ul>
Power	<ul style="list-style-type: none"> <li>PoE : IEEE 802.3af</li> <li>AC adaptor: Input: 100 ~ 240 VAC, Output: 5.9V / 1A (optional)</li> </ul>
Jacks	<ul style="list-style-type: none"> <li>RJ45 10/100 Mbs: LAN port x 1, DC jack x 1, RJ9 Handset jack x 1</li> </ul>
Size and Weight	<ul style="list-style-type: none"> <li>Dimensions: 224 (L) x108mm(W) x 124mm(H), Weight: 770g</li> </ul>

## 3. Regulatory

	USA	EU
EMI	FCC Part 15B	EN55032
Safety		EN 60950-1
EMC		EN55024
		EN61000-3-2
		EN61000-3-3
		IEC61000-4-2
		IEC61000-4-3
RoHS	<ul style="list-style-type: none"> <li>Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)</li> </ul>	
Temperature	<ul style="list-style-type: none"> <li>Storage: Low temperature at -10°C</li> <li>Operating Low temperature at 0°C</li> </ul>	<ul style="list-style-type: none"> <li>High temperature at +60°C</li> <li>High temperature at +40°C</li> </ul>

### Model:

SLN-1103  
 SLN-1203

