

VM-2100-SLT(S)

1 or 2 Lines
Touch Screen

VM-2200-SLT(S)

SIP Phone



- 1 or 2 lines SIP phone.
- Magnetic hook switch.
- Multi language support.
- Full duplex speakerphone.
- 4.3 inch touchable color display.
- Message waiting key with indicator.
- Customizable hotel logo and service dials.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



1. Features

	2200	2100
Keys	<ul style="list-style-type: none"> Dial keys (0~9, *, #) Line keys Line1, Line2 with red color LED Function keys LANGUAGE, EMERGENCY, HOME, REDIAL, SPEKAER, VOLUME +/-, HOLD, MESSAGE 	<ul style="list-style-type: none"> (0~9, *, #) NA LANGUAGE, EMERGENCY, HOME, REDIAL, SPEKAER, VOLUME +/-, MUTE, MESSAGE
Phone Features	<ul style="list-style-type: none"> Touchable 4.3" TFT color display Customizable service menu Redial last call Call Hold and resume(2200 only) Multiple languages support (e.g.: English, French, Spanish, Chinese, Japanese) 	<ul style="list-style-type: none"> Mute and resume(2100 only) Speaker and ringer volume control Red color message key with indicator Ringing indicator Full duplex speaker phone
Display Contents	<ul style="list-style-type: none"> Hotel logo Service menu Language menu Weather (required external information server) Advertising illustration Date and time 	<ul style="list-style-type: none"> Talking time IP address MAC address SIP register status Firmware version Failed network link warning Firmware upgrade via TFTP
Easy Administration	<ul style="list-style-type: none"> Web GUI Auto provisioning via TFTP 	
Codec	<ul style="list-style-type: none"> G.711 	
Network Protocol	<ul style="list-style-type: none"> HTTP server ToS / VLAN IEEE 802.1 p/q 	<ul style="list-style-type: none"> Static IP, DHCP Client
SIP	<ul style="list-style-type: none"> SIP V2 (RFC3261) 	
Security	<ul style="list-style-type: none"> Web login authentication for web setup MD5 for SIP authentication (RFC 2069/ RDC2617) 	
DTMF	<ul style="list-style-type: none"> In-Band / Out-of-Band DTMF(RFC2833) / SIP Info (RFC2976) 	
Voice Quality	<ul style="list-style-type: none"> CNG: Comfortable noise generator Echo canceller: LEC / AEC Jitter buffer/PLC 	
Tones	<ul style="list-style-type: none"> Ring back tone (local), Busy tone, Dial tone 	

2. Hardware Specifications

Display	<ul style="list-style-type: none"> Type: 4.3" resistive touchable WQVGA color TFT with backlight Resolution: 272 x 480 pixels Display size W x H: 55.5mm x 96.7mm
LED Indications	<ul style="list-style-type: none"> Line keys(red), HOLD(red)/MUTE(red), SPEAKER(red), and MESSAGE(red) keys
Power	<ul style="list-style-type: none"> PoE : IEEE 802.3af AC adaptor: Input: 100 ~ 240 VAC, Output: 5V / 1.5A (optional)
Jacks	<ul style="list-style-type: none"> RJ45 10/100 Mbs: LAN port x 1, PC port x1; DC jack x 1, RJ9 Handset jack x 1
Ethernet cable	<ul style="list-style-type: none"> 9 feet x 1
Size and Weight	<ul style="list-style-type: none"> Dimensions: 201mm(L) x132mm(W) x 121mm(H), Weight: 665g (Low profile) Dimensions: 201mm(L) x132mm(W) x 156mm(H), Weight: 670g (High profile)

3. Regulatory

	USA	EU	
EMI	FCC Part 15B	EN55032	
Safety		EN 60950-1	
EMC		EN55024	EC61000-4-4
		EN61000-3-2	EC61000-4-5
		EN61000-3-3	EC61000-4-6
		IEC61000-4-2	EC61000-4-8
		IEC61000-4-3	EC61000-4-11
RoHS	<ul style="list-style-type: none"> Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC) 		
Temperature	<ul style="list-style-type: none"> Storage: Low temperature at -10°C Operating Low temperature at 0°C 	<ul style="list-style-type: none"> High temperature at +60°C High temperature at +40°C 	

Model:

VM-2100-SLT(S)

VM-2200-SLT(S)

