



VX-8108-SMBU(A)

VX-8208-SMBU(A)

1 or 2 Lines  
 Cordless Analog  
 Phone



- 1 or 2 lines cordless phone.
- Full duplex speakerphone.
- Message waiting indicator.
- Pair up to 4 cordless remotes.
- Customizable hotel logo and service dials.
- 3 hard key and 7 scrollable service dials.
- Two USB charging ports



**AEI** brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEI** your satisfaction is our priority.



## 1. Features

### Handset

	8208	8108
Keys	<ul style="list-style-type: none"> <li>Dial keys (0~9, *, #)</li> <li>Line keys Line1, Line2, END</li> <li>Function keys SPEAKER, VOLUME +/-, HOLD, MESSAGE, FRONT DESK, EMERGENCY, and 3 soft keys</li> </ul>	<ul style="list-style-type: none"> <li>(0~9, *, #)</li> <li>Line, END</li> <li>SPEAKER, VOLUME +/-, MUTE, MESSAGE, FRONT DESK, EMERGENCY, and 3 soft keys</li> </ul>
Phone Features	<ul style="list-style-type: none"> <li>One or Two Lines</li> <li>3 hard key and 7 scrollable service dials</li> <li>Call Hold and resume(8208 only)</li> <li>Handset, Speaker, and Ringer volume control</li> </ul>	<ul style="list-style-type: none"> <li>Full duplex speaker phone</li> <li>Mute and resume(8108 only)</li> <li>Red color message waiting indicator for ringing and message waiting</li> </ul>
Display Contents	<ul style="list-style-type: none"> <li>Main logo</li> <li>Service dial list/icons</li> <li>Battery status: power level, charging status</li> </ul>	<ul style="list-style-type: none"> <li>DECT signal status</li> <li>Line status</li> <li>Firmware Version</li> </ul>
Wireless Standard	<ul style="list-style-type: none"> <li>Radio Frequency Range : 2400MHz~2483.5MHz</li> <li>Bit rate : 1150 Kbit/s</li> </ul>	<ul style="list-style-type: none"> <li>Modulation : GFSK</li> <li>Voice coding : 16 Kbit/s</li> <li>RF power : 13 dBm</li> </ul>

### Base

Wireless Standard	<ul style="list-style-type: none"> <li>Radio Frequency Range : 2400MHz~2483.5MHz</li> <li>Bit rate : 1150 Kbit/s</li> </ul>	<ul style="list-style-type: none"> <li>Modulation : GFSK</li> <li>Voice coding : 16 Kbit/s</li> <li>RF power : 13 dBm</li> </ul>
-------------------	---	--

## 2. Hardware Specifications

### Handset

- |                 |   |                          |
|-----------------|---|--------------------------|
| Display         | • 2.0" TFT color display  |                          |
| LED Indications | • Message waiting indicator and keypad backlight                                |                          |
| Power           | • 3.7v / 900 mAh Li-ion battery   | • Standby Time : 240 hrs |
|                 | • Charging Time : 5 hrs   | • Talking Time: 9 hrs    |
| Contact pins    | • 3 contact pins for charging and hook detecting                                |                          |
| Size and Weight | • Dimensions: 190mm(L) x 50mm(W) x 16.5mm mm(H), Weight: 140g(battery included) |                          |

### Base

- |                 |  |
|-----------------|--|
| LED Indications | • Handset charging indicators  |
| Power           | • AC adaptor: Input: 100 ~ 240 VAC, Output: 5V / 3A (5V / 1A for USB charging) |
|                 | • Optional battery backup while power failure                                  |
| Jacks           | • RJ14 PSTN jack x 1, DC jack x 1, USB type A x 2, Reset x 1                   |
| Contact pins    | • 3 contact pins for charging and hook detecting                               |
| Ethernet cable  | • 10 feet x 1  |
| Size and Weight | • Dimensions:115.7mm(L) x104.5mm(W) x 98.8mm(H), Weight: 340g(Base only)       |
|                 | • Dimensions:115.7mm(L) x104.5mm(W) x 190mm(H), Weight: 480g(Handset and base) |

## 3. Regulatory

China

CCC

- |             |   |                           |
|-------------|---|---------------------------|
| RoHS        | • Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC) |                           |
| Temperature | • Storage: Low temperature at -10°C   | High temperature at +60°C |
|             | • Operating Low temperature at 0°C  | High temperature at +40°C |

### Model:

VX-8108-SMBU(A)-VBVH

VX-8208-SMBU(A)-VBVH

