

VM-7108-S(S)

One-Line
Corded VoIP
Speakerphone



Features

Key

- Dial keys (0-9, *, #)
- Line keys N/A
- Function keys REDIAL, SPEAKER, VOLUME +/-, MUTE, MESSAGE, 8 service dial keys

Phone Features

- 8 customizable service dials
- Call Hold and resume (7208 only)
- Handset, speaker and ringer volume control
- Redial last call
- Mute and resume (7108 only)
- Red color message key with indicator
- Ringing indicator
- Full duplex speaker phone

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



PRODUCT OPTIONS



VM-7108-S(S)
One-Line Corded Telephone. Single dialing pad

SPECIFICATIONS

<p>Software</p> <p>Display Contents</p> <p>Easy Administration</p> <p> Codec</p> <p> Network Protocol</p> <p> SIP</p> <p> Security</p> <p> DTMF</p> <p> Voice Quality</p> <p> Tones</p> <p>Hardware</p> <p>Display</p> <p>LED Indications</p> <p>Power</p> <p>Jacks</p> <p>Ethernet cable</p> <p>Size and Weight</p> <p>Stand</p> <p>Power</p> <p>Jacks</p> <p>Regulatory</p> <p>EMI</p> <p>Safety</p> <p>EMC</p> <p>RoHS</p> <p>Temperature</p>	<ul style="list-style-type: none"> • Talking time • IP Address • MAC Address • Web GUI • Auto provisioning via TFTP • G.711 • HTTP / DHCP server • Static IP / DHCP IP assignment • SIP V2 (RFC3261) • Web login authentication for web setup • Md5 for SIP authentication (RFC 2069 / RDC2617) • In-Band / Out-of-Band DTMF (RFC2833) / SIP Info (RFC2976) • CNG: Comfortable noise generator • Echo canceller: LEC / AEC • Jitter buffer / PLC • Ring back tone (local), Busy tone, Dial tone • SIP Register Status • Firmware Version • Failed Network link Warning • Firmware upgrade via TFTP • ToS / VLAN IEEE 802.1 p/q • Dot matrix LCM 16 x 2 with backlight • Line keys (red), HOLD (red) / MUTE (red), SPEAKER (red), and MESSAGE (red) keys • PoE module: IEEE 802.3af • RJ45 10/100 Mbs: LAN poert x 1, PC port x 1; DC jack x 1 (for stand), Rj9 Handset jack x 1 • 9 feet x 1 • Dimensions: 201mm (L) x 132mm (W) x 121mm (H), Weight: TBD (Low profile) • Dimensions: 201mm (L) x 132mm (W) x 156mm (H), Weight: TBD (High profile) • USB output: DC 5V / 0.9A (MAX) • USB type A x 2 USA: FCC Part 15B EU: EN 60950-1 EU: EN 55024 EN 61000-3-2 EN 61000-3-3 EN 61000-4-2 EN 61000-4-3 EU: En55032 IEC 61000-4-4 IEC 61000-4-5 IEC 61000-4-6 IEC 61000-4-11 • Comply with directive 2002 / 95 / EC RoHS (as amended by commission decision 2005 / 613 / EC) • Storage: Low temperature at -10 C High temperature at +60 C • Operating: Low temperature at 0 C High temperature at +40 C
---	---