

Serving the Hospitality Industry with Advanced IP and Analog Telephony Solutions Worldwide

AGR-8106-SMK AGR-8206-SMK 1 or 2 Lines Cordless Analog Phone





- 1 or 2 lines cordless phone.
- Dual keypads dialing.
- Full duplex speakerphone.
- Message waiting indicator.
- Pair up to 4 cordless remotes.
- 6 customizable service dials.
- Faceplate with customizable hotel logo.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality,impeccable workmanship and stylish products.

At AEi your satisfaction is our priority.





AEI - Corporate

Millbrae, California, U.S.A +1.650.552.9416 sales@aeicommunications.com

AEI - EMEA

London, United Kingdom +44.(0).1753.643736 emea@aeicommunications.com

AEI - Asia Pacific

New Taipei City, Taiwan +886.2.2696.8809 asiapac@aeicommunications.com

AEI - Southern Asia

Penang, Malaysia +60.4.399.4341 so.asia@aeicommunications.com

1. Features

н	а	n	d	9	et
	а		u	3	Cι

Keys		8206		8106
	 Dial keys 	(0~9, *, #)		(0~9, *, #)
	 Line keys 	Line1, Line2, END		Line, END
	 Function keys 	Hold, Speaker, Volume, 6 Service		Mute, Speaker, Volume, 6 Service
		dial keys		dial keys
Phone Features	One or Two Lines			6 programmable service dials
	 Call Hold and resume(8206 only) 			Mute and resume(8106 only)
	 Handset, Speaker, and Ringer volume control 			Red color message waiting indicator
	 Full duplex speaker phone 			for ringing and message waiting
Display Contents	 Main logo 		•	Wireless signal status
	Service dial list/icons			Line status
	 Battery status: power level, charging status 			Firmware Version
Wireless Standard	Radio Frequency Range : 2400MHz~2483.5MHz			Modulation : GFSK
				Voice coding: 16 Kbit/s
<u></u>	 Bit rate : 1150 l 	Kbit/s	•	RF power: 13 dBm

Base

Keys		8206	8106	
	 Dial keys 	(0~9, *, #)	(0~9, *	·, #)
	 Line keys 	Line1, Line2, END	Line, E	END
	 Function keys 	Hold, Speaker, Volume, 6 Service	Mute,	Speaker, Volume, 6 Service
		dial keys	dial ke	ys
Phone Features	One or Two Lin	es	• 6 prog	rammable service dials
	Call Hold and r	esume(8206 only)	 Mute a 	and resume(8106 only)
	 Speaker, and R 	inger volume control	 Red co 	olor message waiting indicator
	 Full duplex spe 	aker phone	for ring	ging and message waiting
Wireless Standard	 Radio Frequen 	cy Range: 2400MHz~2483.5MHz	 Modula 	ation:GFSK
	 Bit rate : 1150 	Kbit/s	 Voice 	coding: 16 Kbit/s
			RF por	wer: 13 dBm



AEI - Corporate

Millbrae, California, U.S.A +1.650.552.9416 sales@aeicommunications.com

AEI - EMEA

London, United Kingdom +44.(0).1753.643736 emea@aeicommunications.com

AEI - Asia Pacific

New Taipei City, Taiwan +886.2.2696.8809 asiapac@aeicommunications.com

AEI - Southern Asia

Penang, Malaysia +60.4.399.4341 so.asia@aeicommunications.com

Standby Time: 240 hrs Talking Time: 9 hrs

2. Hardware Specifications

Handset

Display

- 1.8" TFT color display
- LED Indications

Contact pins

- Message waiting indicator and keypad backlight
- Power
- 3.7v / 900 mAh Li-ion battery
- Charging Time: 5 hrs
- 3 contact pins for charging, hook detecting and auto-pairing

Base

LED Indications

Size and Weight

• Line keys, Hold/Mute, Speaker keys, Message waiting, and Handset charging indicators

Dimensions: 175mm(L) x 50mm(W) x 24mm(H), Weight: 180g(battery included)

- Power AC adaptor: Input: 100 ~ 240 VAC, Output: 5.9V / 1A
- Jacks
- ks RJ14 PSTN jack x 1, DC jack x 1
- Contact pins
- 3 contact pins for charging, hook detecting and auto-pairing
- Line cord
- 10 feet x 1
- Size and Weight
- Dimensions:193mm(L) x109mm(W) x 102mm(H), Weight: 430g
- Dimensions:193mm(L) x109mm(W) x 111mm(H), Weight: 610g (handset included)

3. Regulatory

China CCC

RoHS Temperature

- Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)
- Storage: Low temperature at -10°C
- High temperature at +60°C
- Operating Low temperature at 0°C

High temperature at +40°C

Model:

AGR-8106-SMK-VBVH AGR-8206-SMK-VBVH





