

AGR-8106-SMK

AGR-8206-SMK

1- or 2- Line Cordless
Analog DECT Master Phone



AGR-8106-SMK

- Dual keypad dialing.
- Magnetic hook switch.
- Message waiting indicator.
- Full duplex speakerphone.
- Pair up to 4 cordless remotes.
- Faceplate with customizable hotel logo.
- Up to 6 customizable guest service keys.



AGR-8206-SMK

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



1. Features

Handset

Keys	8206	8106
	<ul style="list-style-type: none"> Dial keys (0~9, *, #) Line keys Line1, Line2, END Function keys HOLD, SPEAKER, VOLUME, 6 guest service keys 	<ul style="list-style-type: none"> (0~9, *, #) Line, END MUTE, SPEAKER, VOLUME, 6 guest service keys
Phone Features	<ul style="list-style-type: none"> Up to 6 programmable guest service keys Call hold and resume (8206) Red color message waiting indicator for ringing and message waiting 	<ul style="list-style-type: none"> Full duplex speaker phone Mute and unmute (8106) Handset, speaker, and ringer volume control
Display Contents	<ul style="list-style-type: none"> Main logo Service dial list/icons Battery status: power level, charging status 	<ul style="list-style-type: none"> DECT signal status Line status Firmware version
DECT Standard	<ul style="list-style-type: none"> DECT / CAT iq 2.0 compatible Radio Frequency Range : 1880~1930 MHz EU : 1881.792(ch0)~1897.344(ch9) 10 channels US : 1921.536(ch0)~1928.448(ch4) 5 channels JP : 1895.616(ch0)~1902.528(ch4) 5 channels 	<ul style="list-style-type: none"> Channel Space : 1728 KHz Bit rate : 1150 Kbit/s Modulation : GFSK Voice coding : 16 Kbit/s RF power : 7 dBm

Base

Keys	8206	8106
	<ul style="list-style-type: none"> Dial keys (0~9, *, #) Line keys Line1, Line2, END Function keys HOLD, SPEAKER, VOLUME, 6 guest service keys 	<ul style="list-style-type: none"> (0~9, *, #) Line, END MUTE, SPEAKER, VOLUME, 6 guest service keys
Phone Features	<ul style="list-style-type: none"> Up to 6 programmable guest service keys Call hold and resume (8206) Red color message waiting indicator for ringing and message waiting 	<ul style="list-style-type: none"> Full duplex speaker phone Mute and unmute (8106) Speaker and ringer volume control
DECT Standard	<ul style="list-style-type: none"> DECT / CAT iq2.0 compatible Radio Frequency Range : 1880~1930 MHz EU : 1881.792(ch0)~1897.344(ch9) 10 channels US : 1921.536(ch0)~1928.448(ch4) 5 channels JP : 1895.616(ch0)~1902.528(ch4) 5 channels 	<ul style="list-style-type: none"> Channel Space : 1728 KHz Bit rate : 1150 Kbit/s Modulation : GFSK Voice coding : 16 Kbit/s RF power : 17 dBm

2. Hardware Specifications

Handset

Display	• 1.8" TFT color display	
LED Indications	• Message waiting indicator and keypad backlight	
Power	• 3.7v / 900mAh Li-ion battery	• Standby time: 240hrs
	• Charging time: 5hrs	• Talking time: 9hrs
Contact pins	• 3 contact pins for charging, hook detecting and auto-pairing	
Size and Weight	• Dimensions: 175mm(L) x 50mm(W) x 24mm(H), Weight: 180g(battery included)	

Base

LED Indications	• Line keys, HOLD/MUTE, SPEAKER keys, message waiting, and handset charging indicators
Power	• AC adaptor: Input: 100 ~ 240 VAC, Output: 5.9V / 1A
Jacks	• RJ14 PSTN jack x 1, DC jack x 1
Contact pins	• 3 contact pins for charging, hook detecting and auto-pairing
Line cord	• 10 feet x 1
Size and Weight	• Dimensions: 193mm(L) x 109mm(W) x 102mm(H), Weight: 430g
	• Dimensions: 193mm(L) x 109mm(W) x 111mm(H), Weight: 610g (handset included)

3. Regulatory

	USA	EU
RF	FCC Part 15D	EN 301489-1/-6
EMI	FCC Part 15B	EN 300386
SAR		EN 62479
Safety		EN 62368-1
EMC		EN 301406
PSTN	TIA/EIA 968-B compliant	
RoHS	Comply with directive 2011/65/EU	
Temperature	<ul style="list-style-type: none"> Storage: Low temperature at -10°C Operating: Low temperature at +5°C 	<ul style="list-style-type: none"> High temperature at +60°C High temperature at +35°C

Model:

AGR-8106-SMK-7979

AGR-8206-SMK-7979

AGR-8106-SMK-N1

AGR-8206-SMK-N1

