

AKD-5100-F

Single Line  
Analog Phone

AKD-5103-F



**AKD-5100-F**



**AKD-5103-F**

- Desk or wall-mountable.
- Customizable hotel logo.
- Message waiting key with indicator.
- Up to 3 customizable guest service keys.
- Support FSK message waiting signal type.

**AEi** brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



## 1. Features

|                | Keys                                                                                                                                                                                       | 5100        | 5103                                                                                                                                                                                                                |
|----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                |                                                                                                                                                                                            | (0~9, *, #) | (0~9, *, #)                                                                                                                                                                                                         |
|                | <ul style="list-style-type: none"> <li>Dial keys</li> <li>Function keys</li> <li>Service keys</li> </ul>                                                                                   | N/A         | FLASH, REDIAL, Volume up/down, Up to 3                                                                                                                                                                              |
| Phone Features | <ul style="list-style-type: none"> <li>Up to 3 programmable guest service keys</li> <li>Redial last call (5103)</li> <li>Programmable flash timing (5103)<br/>100ms,300ms,600ms</li> </ul> |             | <ul style="list-style-type: none"> <li>Desk or wall-mountable</li> <li>Ringer volume switch</li> <li>Handset volume control</li> <li>Red color message waiting indicator for ringing and message waiting</li> </ul> |

## 2. Hardware Specifications

|                 |                                                                                                          |
|-----------------|----------------------------------------------------------------------------------------------------------|
| LED Indications | <ul style="list-style-type: none"> <li>Message waiting indicator</li> </ul>                              |
| Power           | <ul style="list-style-type: none"> <li>Telephone line powered</li> </ul>                                 |
| Ring Voltage    | <ul style="list-style-type: none"> <li>40V RMS minimum</li> </ul>                                        |
| MWI type        | <ul style="list-style-type: none"> <li>FSK, high voltage, low voltage, reverse polarity</li> </ul>       |
| Jacks           | <ul style="list-style-type: none"> <li>RJ11 PSTN jack x 1, RJ9 Handset jack x1</li> </ul>                |
| Line cord       | <ul style="list-style-type: none"> <li>6 feet x 1</li> </ul>                                             |
| Size and Weight | <ul style="list-style-type: none"> <li>Dimensions:222mm(L) x108mm(W) x 128mm(H), Weight: 655g</li> </ul> |

## 3. Regulatory

|             | USA                                                                                                                             | EU                                                                                                             |
|-------------|---------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------|
| EMC         | FCC Part 15B                                                                                                                    | EN 55032 & EN 55035<br>EN 62368-1                                                                              |
| PSTN        | TIA/EIA 968-B compliant                                                                                                         |                                                                                                                |
| RoHS        | Comply with directive 2011/65/EU                                                                                                |                                                                                                                |
| Temperature | <ul style="list-style-type: none"> <li>Storage: Low temperature at -10°C</li> <li>Operating: Low temperature at +5°C</li> </ul> | <ul style="list-style-type: none"> <li>High temperature at +60°C</li> <li>High temperature at +35°C</li> </ul> |

Model:

AKD-5100-F

AKD-5103-F

