

AKD-5100-F

Single Line  
Analog Phone

AKD-5103-F



**AKD-5100-F**



**AKD-5103-F**

- Desk or wall-mountable.
- Customizable hotel logo.
- Message waiting key with indicator.
- Up to 3 customizable guest service keys.
- Support FSK message waiting signal type.

**AEi** brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



### 1. Features

	Keys	5100	5103
		(0~9, *, #)	(0~9, *, #)
		N/A	FLASH, REDIAL, Volume up/down, Up to 3
Phone Features	<ul style="list-style-type: none"> <li>Dial keys</li> <li>Function keys</li> <li>Service keys</li> <li>Up to 3 programmable guest service keys</li> <li>Redial last call (5103)</li> <li>Programmable flash timing (5103) 100ms,300ms,600ms</li> </ul>	N/A	<ul style="list-style-type: none"> <li>Desk or wall-mountable</li> <li>Ringer volume switch</li> <li>Handset volume control</li> <li>Red color message waiting indicator for ringing and message waiting</li> </ul>

### 2. Hardware Specifications

LED Indications	<ul style="list-style-type: none"> <li>Message waiting indicator</li> </ul>
Power	<ul style="list-style-type: none"> <li>Telephone line powered</li> </ul>
Ring Voltage	<ul style="list-style-type: none"> <li>40V RMS minimum</li> </ul>
MWI type	<ul style="list-style-type: none"> <li>FSK, high voltage, low voltage, reverse polarity</li> </ul>
Jacks	<ul style="list-style-type: none"> <li>RJ11 PSTN jack x 1, RJ9 Handset jack x1</li> </ul>
Line cord	<ul style="list-style-type: none"> <li>10 feet x 1</li> </ul>
Size and Weight	<ul style="list-style-type: none"> <li>Dimensions:222mm(L) x108mm(W) x 128mm(H), Weight: 655g</li> </ul>

### 3. Regulatory

	USA	EU
EMC	FCC Part 15B	EN 55032 & EN 55035 EN 62368-1
PSTN	TIA/EIA 968-B compliant	
RoHS	Comply with directive 2011/65/EU	
Temperature	<ul style="list-style-type: none"> <li>Storage: Low temperature at -10°C</li> <li>Operating: Low temperature at +5°C</li> </ul>	<ul style="list-style-type: none"> <li>High temperature at +60°C</li> <li>High temperature at +35°C</li> </ul>

**Model:**

**AKD-5100-F**

**AKD-5103-F**

