

AMT-6110-S

Single Line
Analog Phone



AMT-6110-S

- Hearing aid support.
- Desk or wall-mountable.
- Handsfree speakerphone.
- Message waiting indicator.
- Faceplate with customizable hotel logo.
- Up to 10 customizable guest service keys.

AEI brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEI** your satisfaction is our priority.



1. Features

- | | | |
|----------------|---|--|
| Keys | <ul style="list-style-type: none"> • Dial keys (0~9, *, #) • Function keys REDIAL, FLASH, MUTE, SPEAKER, MESSAGE, Volume up/down, 10 guest service keys | |
| Phone Features | <ul style="list-style-type: none"> • Desk or wall-mountable • Selectable flash timing • Mute and unmute • Redial last call • Up to 10 programmable guest service keys and 1 programmable message key | <ul style="list-style-type: none"> • Handset, Speaker volume control • Ringer volume switch • Red color message waiting indicator for ringing and message waiting |

2. Hardware Specifications

- | | |
|-----------------------------|--|
| LED Indications | • Line keys, CONF, MUTE, SPEAKER keys, and message waiting indicator |
| Power | • Telephone line powered |
| Jacks | • RJ11 PSTN jack x 1, RJ9 Handset jack x1, |
| Ring Voltage | • 40V RMS minimum |
| Message waiting signal type | • High voltage, low voltage, reverse polarity |
| Line cord | • 6 feet x 1 |
| Size and Weight | • Dimensions:227mm(L) x158mm(W) x 141mm(H), Weight: 835g |

3. Regulatory

	USA	EU
EMC	FCC Part 15B	EN55032 & EN55035 EN62368-1
PSTN	TIA/EIA 968-B compliant	
RoHS	Comply with directive 2011/65/EU	
Temperature	<ul style="list-style-type: none"> • Storage: Low temperature at -10°C • Operating: Low temperature at +5°C 	<ul style="list-style-type: none"> High temperature at +60°C High temperature at +35°C

Model:
AMT-6110-S

