

ASP-6110-SF

Single Line  
Analog Phone



- Single line analog phone.
- Half duplex speakerphone.
- 10 customizable service dials.
- Message waiting key with indicator.
- Customizable hotel logo and service dials.
- Support FSK Message Waiting Signal Type

**AEi** brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



## 1. Features

Keys	<ul style="list-style-type: none"> <li>☐ Dial keys (0~9, *, #)</li> <li>☐ Function keys Speaker, Mute, Redial, Flash, Message and Volume up/down</li> <li>☐ Programmable Keys 10 Service dial keys</li> </ul>
Phone Features	<ul style="list-style-type: none"> <li>☐ Mute and Resume</li> <li>☐ 10 programmable services dials</li> <li>☐ Programmable flash timing</li> <li>☐ Red color message waiting indicator for ringing and message waiting</li> <li>☐ Handset, Speaker volume control</li> <li>☐ Ringer volume switch</li> <li>☐ Redial last call</li> </ul>

## 2. Hardware Specifications

LED Indications	☐ Speaker, Mute keys and Message waiting indicator
Power	☐ Telephone line powered
Jacks	☐ RJ11 PSTN jack x 2, RJ9 Handset jack x1,
Ring Voltage	☐ 40V RMS minimum
Line Cord	☐ 10 feet x 1
Size and Weight	☐ Dimensions: 227mm(L) x 158mm(W) x 141mm(H), Weight: 835g
Message Waiting Signal Type	● FSK, High Voltage, Low Voltage, Reverse Polarity

## 3. Regulatory

	USA	EU
PSTN	Part 68	TBR 21
EMC	FCC Part 15B	EN55032 & EN55024
RoHS	☐ Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)	
Temperature	☐ Storage: Low temperature at -10°C	High temperature at +60°C
	☐ Operating: Low temperature at 0°C	High temperature at +40°C

**Model:**

**ASP-6110-SF**

