

ASP-6110-SF

Single Line
Analog Phone



- Hearing aid support.
- Handsfree speakerphone.
- 10 customizable service dials.
- Message waiting key with indicator.
- Customizable hotel logo and service dials.
- Support FSK message waiting signal type.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



1. Features

- | | |
|----------------|---|
| Keys | <ul style="list-style-type: none"> ● Dial keys (0-9, *, #) ● Line keys N/A ● Function keys Redial, Flash, Mute, Speaker, Message, Volume up/down, 10 Service dial keys |
| Phone Features | <ul style="list-style-type: none"> ● 3-Way Conference (6210 only) ● Call Hold and resume (6210 only) ● Mute and unmute ● Red color message waiting indicator for ringing and message waiting ● 10 programmable service dials ● Selectable flash timing (6110 only) ● Handset, Speaker volume control ● Ringer volume switch ● Redial last call |

2. Hardware Specifications

- | | |
|-----------------------------|--|
| LED Indications | ● Line keys, Conf, Mute, Speaker keys, and Message waiting indicator |
| Power | ● Telephone line powered |
| Jacks | ● RJ11 PSTN jack x 2, RJ9 Handset jack x1, |
| Ring Voltage | ● 40V RMS minimum |
| Message waiting signal type | ● FSK, high voltage, low voltage, reverse polarity |
| Line cord | ● 10 feet x 1 |
| Size and Weight | ● Dimensions:227mm(L) x158mm(W) x 141mm(H), Weight: 835g |

3. Regulatory

	USA	EU
EMC	FCC Part 15B	EN55032 & EN55035 EN62368-1
RoHS	● Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)	
Telecom	● TIA/EIA 968-B compliant	
Temperature	● Storage: Low temperature at -10°C	High temperature at +60°C
	● Operating Low temperature at +5°C	High temperature at +35°C

Model:
ASP-6110-SF

