

# Serving the Hospitality Industry with Advanced IP and Analog Telephony Solutions Worldwide

GR-8106-SPB

GR-8206-SPB

1 or 2 Lines Cordless Handset phone





- 1 or 2 lines cordless handset.
- Full duplex speakerphone.
- Message waiting indicator.
- Customizable hotel logo and service dials.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality,impeccable workmanship and stylish products.

At AEi your satisfaction is our priority.





### **AEi-Corporate Office**

Carrollton, Texas, U.S.A Sales: +1.254.335.0555 sales@aeicommunications.com

#### AEi-EMEA Office

London, United Kindom Sales: +44 (0)1753.643736 emea@aeicommunications.com

#### **AEi-Asia Pacific Office**

New Taipei City, Taiwan Sales: +886.2.2696.8809 asiapac@aeicommunications.com

#### AEi-CEE&CIS Office

Budva, Montenegro Sales: +382 69 891 251 eastern.europe@aeicommunications.com

# **AEi-Corporate Office**

Standby Time: 240 hrs

Talking Time: 9 hrs

Penang, Malaysia Sales: +604.3994341 so.asia@aeicommunications.com

### 1. Features

## Handset

Keys 8206 8106 (0~9, \*, #) Dial keys (0~9, \*, #) Line keys Line1, Line2, END Line, END Function keys Hold, Speaker, Volume, 6 Service Mute, Speaker, Volume, 6 Service dial keys dial keys Phone Features One or Two Lines 6 programmable service dials Call Hold and resume(8206 only) Mute and resume(8106 only) Handset, Speaker, and Ringer volume control Red color message waiting indicator Full duplex speaker phone for ringing and message waiting Display Contents Main logo **DECT** signal status Service dial icons Line status Battery status: power level, charging status Firmware Version **DECT Standard** DECT / CAT iq2.0 compatible Channel Space: 1728 KHz Radio Frequency Range: 1880~1930 MHz Bit rate: 1150 Kbit/s EU: 1881.792(ch0)~1897.344(ch9) 10 Channels Modulation: GFSK US: 1921.536(ch0)~1928.448(ch4) 5 Channels Voice coding: 16 Kbit/s JP: 1895.616(ch0)~1902.528(ch4) 5 Channels RF power: 7 dBm

# 2. Hardware Specifications

#### Handset

Display 1.8" TFT color display

LED Indications Message waiting indicator and keypad backlight

> 3.7v / 900 mAh Li-ion battery Power

> > Charging Time: 5 hrs

Contact pins 3 contact pins for charging and hook detecting

Size and Weight Dimensions: 175mm(L) x 50mm(W) x 24mm(H), Weight: 180g(battery included)

## Stand Cradle

LED Indications

Handset charging indicators

Power AC adaptor: Input: 100 ~ 240 VAC, Output: 5.9V / 1A

Jacks DC jack x 1

Contact pins 3 contact pins for charging and hook detecting

Dimensions:106mm(L) x88mm(W) x 97mm(H), Weight: 290g Size and Weight

Dimensions:106mm(L) x88mm(W) x 179mm(H), Weight: 455g (handset included)

3. Regulatory USA EU FCC Part 15D RF EN301406 FCC Part 15B **EMI** EN300386

SAR EN62479 Safety EN60950-1 **EMC** EN301489-1/6 RoHS Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)

Storage: Low temperature at -10°C High temperature at +60°C Temperature Operating Low temperature at +5°C High temperature at +35°C

Model:

**GR-8106-SPB** 

GR-8206-SPB





