

GR-8106-SPBU

1- or 2- Lines Cordless
Handset Phone

GR-8206-SPBU



GR-8106-SPBU



GR-8206-SPBU

- LCD display on handset.
- Customizable hotel logo.
- Full duplex speakerphone.
- Single USB charging port.
- Message waiting indicator.
- Up to 6 customizable guest service keys.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



1. Features

Handset

	8206	8106
Keys	<ul style="list-style-type: none"> Dial keys (0~9, *, #) Line keys Line1, Line2, END Function keys HOLD, SPEAKER, VOLUME Service Keys Up to 6 	<ul style="list-style-type: none"> (0~9, *, #) Line, END MUTE, SPEAKER, VOLUME Up to 6
Phone Features	<ul style="list-style-type: none"> Up to 6 programmable guest service dial keys Call Hold and resume (8206 only) Handset, Speaker, and Ringer volume control USB type A jack for mobile device charging 	<ul style="list-style-type: none"> Full duplex speaker phone Mute and unmute (8106 only) Red color message waiting indicator for ringing and message waiting
Display Contents	<ul style="list-style-type: none"> Main logo Service dial icons Battery status: power level, charging status 	<ul style="list-style-type: none"> DECT signal status Line status Firmware Version
DECT Standard	<ul style="list-style-type: none"> DECT / CAT iq2.0 compatible Radio Frequency Range : 1880~1930 MHz EU : 1881.792(ch0)~1897.344(ch9) 10 Channels US : 1921.536(ch0)~1928.448(ch4) 5 Channels JP : 1895.616(ch0)~1902.528(ch4) 5 Channels 	<ul style="list-style-type: none"> Channel Space : 1728 KHz Bit rate : 1150 Kbit/s Modulation : GFSK Voice coding : 16 Kbit/s RF power : 7 dBm

2. Hardware Specifications

Handset

Display	<ul style="list-style-type: none"> 1.8" TFT color display 	
LED Indications	<ul style="list-style-type: none"> Message waiting indicator and keypad backlight 	
Power	<ul style="list-style-type: none"> 3.7v / 900mAh Li-ion battery Charging Time: 5hrs 	<ul style="list-style-type: none"> Standby Time: 240hrs Talking Time: 9hrs
Contact pins	<ul style="list-style-type: none"> 3 contact pins for charging and hook detecting 	
Size and Weight	<ul style="list-style-type: none"> Dimensions: 175mm(L) x 50mm(W) x 24mm(H), Weight: 180g(battery included) 	

Stand Cradle

LED Indications	<ul style="list-style-type: none"> Handset charging indicators
Power	<ul style="list-style-type: none"> AC adaptor: Input: 100 ~ 240 VAC, Output: 5V / 3A
Jacks	<ul style="list-style-type: none"> DC jack x 1, USB type A x 1
Contact pins	<ul style="list-style-type: none"> 3 contact pins for charging and hook detecting
Size and Weight	<ul style="list-style-type: none"> Dimensions:106mm(L) x88mm(W) x 97mm(H), Weight: 290g Dimensions:106mm(L) x88mm(W) x 179mm(H), Weight: 455g (handset included)

3. Regulatory

	USA	EU
RF	FCC Part 15D	EN 301489-1/-6
EMI	FCC Part 15B	EN 300386
SAR		EN 62479
Safety		EN 62368-1
EMC		EN 301406
RoHS	<ul style="list-style-type: none"> Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC) 	
Temperature	<ul style="list-style-type: none"> Storage: Low temperature at -10°C Operating: Low temperature at 5°C 	<ul style="list-style-type: none"> High temperature at +60°C High temperature at +35°C

Model:

GR-8106-SPBU

GR-8206-SPBU

