

SAX-8106-P

SAX-8206-P

1- or 2- Line Cordless
Wall-mount Handset Phone



SAX-8106-P



SAX-8206-P

- Magnetic hook switch.
- Customizable hotel logo.
- Message waiting indicator.
- Up to 6 customizable guest service keys.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



1. Features

	8206	8106
Keys	<ul style="list-style-type: none"> Dial keys (0~9, *, #) Line keys Line1, Line2, END Function keys HOLD, MUTE, VOLUME Service keys Up to 6 	<ul style="list-style-type: none"> (0~9, *, #) Line, END HOLD, MUTE, VOLUME Up to 6
Phone Features	<ul style="list-style-type: none"> Up to 6 programmable guest service keys Call hold and resume Handset and ringer volume control 	<ul style="list-style-type: none"> Mute and unmute Red color message waiting indicator for ringing and message waiting
Display Contents	<ul style="list-style-type: none"> Main logo Service dial icon 	<ul style="list-style-type: none"> Line status Firmware version
Tones	<ul style="list-style-type: none"> Ring back tone (local), Busy tone, Dial tone 	
Wireless Standard	<ul style="list-style-type: none"> DECT / CAT-iq 2.0 compatible Radio Frequency Range : 1880~1930 MHz EU : 1881.792(ch0)~1897.344(ch9) 10Channels US : 1921.536(ch0)~1928.448(ch4) 5 Channels JP : 1895.616(ch0)~1902.528(ch4) 5 Channels 	<ul style="list-style-type: none"> Channel Space : 1728 KHz Bit rate : 1150 Kbit/s Modulation : GFSK Voice coding : 16 Kbit/s RF power : 7 dBm

2. Hardware Specifications

Display	<ul style="list-style-type: none"> 1.8" TFT color display
LED Indications	<ul style="list-style-type: none"> Message waiting indicator
DECT Coverage	<ul style="list-style-type: none"> Indoor: 30m ~ 50m(ideal); Outdoor: 300m(ideal); depending on location and environment
Power	<ul style="list-style-type: none"> PoE: IEEE 802.3af compliant AC adaptor: Input: 100 ~ 240 VAC, Output: 5V / 3A (optional)
Jacks	<ul style="list-style-type: none"> RJ45 10/100Mbps: LAN port x 1, DC jack x 1
Ethernet cable	<ul style="list-style-type: none"> 0.5feet x 1
Bungee cord	<ul style="list-style-type: none"> Coiled cord with optional bungee cord (handset anti-drop string)
Size and Weight	<ul style="list-style-type: none"> Dimensions:200mm(L) x82mm(W) x 46mm(H), Weight: 455g

3. Regulatory

	USA	EU
RF	FCC Part 15D	EN 301489-1/-6
EMI	FCC Part 15B	EN 300386
SAR		EN 62479
Safety		EN 62368-1
EMC		EN 301406
RoHS	Comply with directive 2011/65/EU	
Temperature	<ul style="list-style-type: none"> Storage: Low temperature at -10°C Operating: Low temperature at +5°C 	<ul style="list-style-type: none"> High temperature at +60°C High temperature at +35°C

Model:

SAX-8106-P

SAX-8206-P

SAX-8106-PBC

SAX-8206-PBC

