

SKD-1103E

1 or 2 Lines  
SIP Phone

SKD-1203E



- ▣ 1 or 2 lines SIP phone.
- ▣ 3 customizable service dials.
- ▣ Dual Ethernet Ports .
- ▣ Message waiting indicator.
- ▣ Faceplate with customizable hotel logo.

**AEi** brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.





**AEI- Corporate Office**  
 Milbrae, California U.S.A  
 Sales : +1-650-552-9476  
 sales@aeicomcommunications.com

**AEI- CALA Office**  
 Lima, Peru  
 Sales : +51-9-8257-6251  
 cala@aeicomcommunications.com

**AEI- Asia Pacific Office**  
 New Taipei City, Taiwan  
 Sales : +886-2-2696-8809  
 asiapac@aeicomcommunications.com

**AEI- EMEA Office**  
 London, United Kingdom  
 Sales : +44 (0)1753-643736  
 emea@aeicomcommunications.com

**AEI- Southern Asia Office**  
 Penang, Malaysia  
 Sales : +604-3994341  
 so.asia@aeicomcommunications.com

**AEI- CEE&CIS Office**  
 Budva, Montenegro  
 Sales : +3826981251  
 eastern.europe@aeicomcommunications.com

Serving the Hospitality Industry with Advanced IP and Analog Telephony Solutions Worldwide

## 1. Features

	Keys	1203E	1103E
	<ul style="list-style-type: none"> <li><input type="checkbox"/> Dial keys</li> <li><input type="checkbox"/> Line keys</li> <li><input type="checkbox"/> Function keys</li> </ul>	(0~9, *, #) Line1, Line2 with red color LED Hold, Redial, Volume up/down, 3 Service dial keys	(0~9, *, #) N/A Hold, Redial, Volume up/down, 3 Service dial keys
Phone Features	<ul style="list-style-type: none"> <li>● One or Two Lines</li> <li><input type="checkbox"/> 3 programmable speed dial service keys</li> <li><input type="checkbox"/> Red color message waiting indicator for ringing and message waiting</li> </ul>		<ul style="list-style-type: none"> <li><input type="checkbox"/> Handset and ringer volume control</li> <li><input type="checkbox"/> Redial last call</li> <li><input type="checkbox"/> Call Hold and resume</li> <li><input type="checkbox"/> Dual Ethernet Ports</li> </ul>
Easy Administration	<ul style="list-style-type: none"> <li>● Web GUI.</li> <li><input type="checkbox"/> Auto provisioning</li> </ul>		<ul style="list-style-type: none"> <li><input type="checkbox"/> Firmware upgrade via web.</li> </ul>
Codec	<ul style="list-style-type: none"> <li>● G.711</li> </ul>		
Network Protocol	<ul style="list-style-type: none"> <li>● Static IP, DHCP Client</li> <li><input type="checkbox"/> HTTP server</li> </ul>		<ul style="list-style-type: none"> <li><input type="checkbox"/> ToS / VLAN IEEE 802.1 p/q</li> <li><input type="checkbox"/> STUN (RFC 3489)</li> </ul>
SIP	<ul style="list-style-type: none"> <li>● SIP V2 (RFC3261)</li> </ul>		<ul style="list-style-type: none"> <li>● MD5 for SIP authentication (RFC2069/ RFC2617)</li> </ul>
Security	<ul style="list-style-type: none"> <li>● Web login authentication for web setup</li> </ul>		
DTMF	<ul style="list-style-type: none"> <li>● In-Band / Out-of-Band DTMF(RFC2833) / SIP Info (RFC2976)</li> </ul>		
Voice Quality	<ul style="list-style-type: none"> <li>● CNG: Comfortable noise generator.</li> <li><input type="checkbox"/> LEC: Line Echo Canceller.</li> <li><input type="checkbox"/> Jitter buffer.</li> </ul>		
Tones	<ul style="list-style-type: none"> <li>● Ring back tone (local), Busy tone, Dial tone</li> </ul>		

## 2. Hardware Specifications

LED Indications	<ul style="list-style-type: none"> <li>● Line keys and Message waiting indicator</li> </ul>
Power	<ul style="list-style-type: none"> <li>● PoE : IEEE 802.3af</li> <li><input type="checkbox"/> AC adaptor: Input: 100 ~ 240 VAC, Output: 5.9V / 1A (optional)</li> </ul>
Jacks	<ul style="list-style-type: none"> <li>● RJ45 10/100 Mbs: LAN port x 1, DC jack x 1, RJ9 Handset jack x 1</li> </ul>
Ethernet cable	<ul style="list-style-type: none"> <li>● 9 feet x 1</li> </ul>
Size and Weight	<ul style="list-style-type: none"> <li>● Dimensions: 224 (L) x108mm(W) x 124mm(H), Weight: 770g</li> </ul>

## 3. Regulatory

	USA	EU
EMI	FCC Part 15B	EN55032
Safety		EN 60950-1
EMC		EN55024
		EN61000-3-2
		EN61000-3-3
		IEC61000-4-2
		IEC61000-4-3
RoHS	<ul style="list-style-type: none"> <li>● Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)</li> </ul>	
Temperature	<ul style="list-style-type: none"> <li><input type="checkbox"/> Storage: Low temperature at -10°C</li> <li><input type="checkbox"/> Operating Low temperature at 0°C</li> </ul>	High temperature at +60°C High temperature at +40°C

Model:

SKD-1103  
 SKD-1203

