

SLN-1103

1- or 2- Lines  
SIP Phone

SLN-1203



**SLN-1103**



**SLN-1203**

- Message waiting indicator.
- Up to 10 customizable service dials.
- Faceplate with customizable hotel logo.

**AEI** brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEI** your satisfaction is our priority.



## 1. Features

	Keys	1103	1203
		<ul style="list-style-type: none"> <li>Dial keys (0~9, *, #)</li> <li>Line keys N/A</li> <li>Function keys Hold, Redial, Volume up/down, 3 Service dial keys</li> </ul>	<ul style="list-style-type: none"> <li>(0~9, *, #)</li> <li>Line1, Line2 with red color LED</li> <li>Hold, Redial, Volume up/down, 3 Service dial keys</li> </ul>
Phone Features		<ul style="list-style-type: none"> <li>Up to 10 programmable service dial keys</li> <li>Red color message waiting indicator for ringing and message waiting</li> </ul>	<ul style="list-style-type: none"> <li>Handset and ringer volume control</li> <li>Redial last call</li> <li>Call Hold and resume</li> <li>Firmware upgrade via web.</li> </ul>
Easy Administration		<ul style="list-style-type: none"> <li>Web GUI.</li> <li>Auto provisioning</li> </ul>	
Codec		<ul style="list-style-type: none"> <li>G.711 (a-law, <math>\mu</math>-law)</li> </ul>	
Network Protocol		<ul style="list-style-type: none"> <li>HTTP server</li> <li>ToS / VLAN IEEE 802.1 p/q</li> </ul>	<ul style="list-style-type: none"> <li>Static IP, DHCP Client</li> </ul>
SIP		<ul style="list-style-type: none"> <li>SIP V2 (RFC3261)</li> </ul>	
Security		<ul style="list-style-type: none"> <li>Web login authentication for web setup</li> <li>TLS 1.2</li> </ul>	<ul style="list-style-type: none"> <li>MD5 for SIP authentication (RFC2069/ RFC2617)</li> </ul>
DTMF		<ul style="list-style-type: none"> <li>In-Band / Out-of-Band DTMF(RFC2833) / SIP Info (RFC2976)</li> </ul>	
Voice Quality		<ul style="list-style-type: none"> <li>CNG: Comfortable noise generator</li> <li>Echo canceller: LEC / AEC</li> <li>Jitter buffer/PLC</li> </ul>	
Tones		<ul style="list-style-type: none"> <li>Ring back tone (local), Busy tone, Dial tone</li> </ul>	

## 2. Hardware Specifications

LED Indications	<ul style="list-style-type: none"> <li>Line keys (1203), Message waiting indicator</li> </ul>
Power	<ul style="list-style-type: none"> <li>PoE: IEEE 802.3af compliant</li> <li>AC adaptor: Input: 100 ~ 240 VAC, Output: 5.9V / 1A (optional)</li> </ul>
Jacks	<ul style="list-style-type: none"> <li>RJ45 10/100 Mbs: LAN port x 1, DC jack x 1, RJ9 Handset jack x 1</li> </ul>
Ethernet cable	<ul style="list-style-type: none"> <li>9 feet x 1</li> </ul>
Size and Weight	<ul style="list-style-type: none"> <li>Dimensions: 224 (L) x108mm(W) x 124mm(H), Weight: 770g</li> </ul>

## 3. Regulatory

	USA	EU
EMI	FCC Part 15B	EN 55032
Safety		EN 62368-1
EMC		EN 55035
RoHS	<ul style="list-style-type: none"> <li>Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)</li> </ul>	
Temperature	<ul style="list-style-type: none"> <li>Storage: Low temperature at -10°C</li> <li>Operating Low temperature at +5°C</li> </ul>	<ul style="list-style-type: none"> <li>High temperature at +60°C</li> <li>High temperature at +35°C</li> </ul>

### Model:

SLN-1103

SLN-1203

