

VM-6108-SF(A)

Single line  
Analog Phone



- Hearing aid support.
- Magnetic hook switch.
- Handsfree speakerphone.
- 8 customizable service dials.
- Message key with waiting indicator.
- Faceplate with customizable hotel logo.
- Support FSK message waiting signal type.

**AEi** brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



## 1. Features

Keys	<ul style="list-style-type: none"> <li>Dial keys (0~9, *, #)</li> <li>Function keys Redial, Speaker, Volume +/-, Mute, Message, 8 service dial keys</li> </ul>
Phone Features	<ul style="list-style-type: none"> <li>Single line telephone system with speakerphone</li> <li>Adjustable High-low ringer (2-way selectable switch)</li> <li>7 steps speakerphone digital volume control</li> <li>8 programmable Guest Service Keys and 1 programmable message key</li> <li>4 steps handset digital volume control</li> <li>Tone dialing only</li> <li>Multi-Purpose LED indicator for Message Waiting and Incoming Ring</li> <li>Last number redial (Max up to 31 digitals)</li> <li>Microphone Mute with LED indicator</li> <li>Hearing Aid Receiver Compatible</li> <li>PBX / Standard Line compatible</li> </ul>

## 2. Hardware Specifications

LED Indications	<ul style="list-style-type: none"> <li>MUTE (red), SPEAKER (red), and MESSAGE (red) keys</li> </ul>
Power	<ul style="list-style-type: none"> <li>Telephone line powered</li> </ul>
Jacks	<ul style="list-style-type: none"> <li>RJ14(RJ11) PSTN jack x 1, RJ9 Handset jack x 1</li> </ul>
Ring Voltage	<ul style="list-style-type: none"> <li>40V RMS minimum</li> </ul>
Message waiting signal type	<ul style="list-style-type: none"> <li>FSK, high voltage, low voltage, reverse polarity</li> </ul>
Line cord	<ul style="list-style-type: none"> <li>10 feet x 1</li> </ul>
Size and Weight	<ul style="list-style-type: none"> <li>Dimensions: 201mm(L) x 132mm(W) x 121mm(H), Weight: 600g</li> </ul>

## 3. Regulatory

	USA	EU
EMC	FCC Part 15B	EN55032 & EN55035 EN62368-1
RoHS	Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)	
Telecom	TIA/EIA 968-B compliant	
Temperature	<ul style="list-style-type: none"> <li>Storage: Low temperature at -10°C</li> <li>Operating Low temperature at +5°C</li> </ul>	<ul style="list-style-type: none"> <li>High temperature at +60°C</li> <li>High temperature at +35°C</li> </ul>

**Model:**  
**VM-6108-SF(A)**

