


VM-8108-SMK(A)

VM-8208-SMK(A)

1- or 2- Lines Cordless
 Analog DECT Phone



VM-8108-SMK(A)



VM-8208-SMK(A)

- Magnetic hook switch.
- Full duplex speakerphone.
- Pair up to 4 cordless remotes.
- Message waiting key with indicator.
- Faceplate with customizable hotel logo.
- Up to 8 customizable guest service keys.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At AEi your satisfaction is our priority.



1. Features

Handset

	8208	8108
Keys	<ul style="list-style-type: none"> Dial keys (0~9, *, #) Line keys Line1, Line2, END Function keys SPEAKER, VOLUME +/-, HOLD, MESSAGE, GUEST SERVICES, EMERGENCY, and 3 soft keys 	<ul style="list-style-type: none"> (0~9, *, #) Line, END SPEAKER, VOLUME +/-, MUTE, MESSAGE, GUEST SERVICES, EMERGENCY, and 3 soft keys
Phone Features	<ul style="list-style-type: none"> 3 hard key and 7 scrollable service dials Call Hold and resume(8208 only) Handset, Speaker, and Ringer volume control Red color message waiting indicator for ringing and message waiting 	<ul style="list-style-type: none"> Full duplex speaker phone Mute and unmute(8108 only)
Display Contents	<ul style="list-style-type: none"> Main logo Service dial list/icons Battery status: power level, charging status 	<ul style="list-style-type: none"> DECT signal status Line status Firmware Version
DECT Standard	<ul style="list-style-type: none"> DECT / CAT iq2.0 compatible Radio frequency range : 1880~1930 MHz EU: 1881.792(ch0)~1897.344(ch9) 10 channels US: 1921.536(ch0)~1928.448(ch4) 5 channels JP: 1895.616(ch0)~1902.528(ch4) 5 Channels 	<ul style="list-style-type: none"> Channel space : 1728 KHz Bit rate : 1150 Kbit/s Modulation : GFSK Voice coding : 16 Kbit/s RF power : 7 dBm

Base

	8208	8108
Keys	<ul style="list-style-type: none"> Dial keys (0~9, *, #) Line keys Line1, Line2 with red color LED Function keys REDIAL, SPEAKER, VOLUME +/-, HOLD, MESSAGE, 8 guest service keys 	<ul style="list-style-type: none"> (0~9, *, #) N/A REDIAL, SPEAKER, VOLUME +/-, MUTE, MESSAGE, 8 guest service keys
Phone Features	<ul style="list-style-type: none"> 8 customizable service dials Call Hold and resume(8208 only) Handset, speaker and ringer volume control Red color message key with indicator 	<ul style="list-style-type: none"> Mute and unmute(8108 only) Redial last call Ringing indicator Full duplex speaker phone
DECT Standard	<ul style="list-style-type: none"> DECT / CAT iq2.0 compatible Radio frequency range : 1880~1930 MHz EU: 1881.792(ch0)~1897.344(ch9) 10 channels US: 1921.536(ch0)~1928.448(ch4) 5 channels JP: 1895.616(ch0)~1902.528(ch4) 5 Channels 	<ul style="list-style-type: none"> Channel space : 1728 KHz Bit rate : 1150 Kbit/s Modulation : GFSK Voice coding : 16 Kbit/s RF power : 17 dBm

2. Hardware Specifications

Handset

- Display • 2.0" TFT color display
- LED Indications • Message waiting indicator and keypad backlight
- Power • 3.7v / 900mAh Li-ion battery
 - Standby Time: 240hrs
 - Charging Time: 5hrs
 - Talking Time: 9hrs
- Contact pins • 3 contact pins for charging, hook detecting and auto-pairing
- Size and Weight • Dimensions: 190mm(L) x 50mm(W) x 16.5mm mm(H), Weight: 140g(battery included)

Base

- LED Indications • Line keys(red), HOLD(red)/MUTE(red), SPEAKER(red), and MESSAGE(red) keys
- Power • AC adaptor: Input: 100 ~ 240 VAC, Output: 5V / 3A
- Jacks • RJ14(RJ11) PSTN jack x 1, DC jack x 1
- Contact pins • 3 contact pins for charging and hook detecting.
- Line cord • 10 feet x 1
- Size and Weight • Dimensions: 201mm(L) x132mm(W) x 121mm(H), Weight: 510g

3. Regulatory

	USA	EU
RF	FCC Part 15D	EN 301489-1/-6
EMI	FCC Part 15B	EN 300386
Safety		EN 62368-1
EMC		EN 301406
SAR		EN 62479
PSTN	TIA-968-B	
RoHS	• Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)	
Temperature	• Storage: Low temperature at -10°C	High temperature at +60°C
	• Operating: Low temperature at +5°C	High temperature at +35°C

Model:

VM-8108-SMK(A)

VM-8208-SMK(A)

