

VM-9100-SLT(S)

1 or 2 Lines
Touch Screen
SIP Phone

VM-9200-SLT(S)



- 1 or 2 lines SIP phone.
- Magnetic hook switch.
- 4.3 inch touch screen.
- Multi language support
- Full duplex speakerphone.
- Message waiting key with indicator.
- Customizable hotel logo and service dials.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



1. Features

	Keys	9200	9100
	<ul style="list-style-type: none"> Dial keys Line keys Function keys 	(0~9, *, #) Line1, Line2 with red color LED LANGUAGE, EMERGENCY, HOME, REDIAL, SPEKAER, VOLUME +/-, HOLD, MESSAGE	(0~9, *, #) N/A LANGUAGE, EMERGENCY, HOME, REDIAL, SPEKAER, VOLUME +/-, MUTE, MESSAGE
Phone Features	<ul style="list-style-type: none"> 4.3" TFT color touch screen Customizable service menu Redial last call Call Hold and resume(9200 only) Multiple languages support (e.g.: English, French, Spanish, Chinese, Japanese) 		<ul style="list-style-type: none"> Mute and resume(9100 only) Speaker and ringer volume control Red color message key with indicator Ringing indicator Full duplex speaker phone
Display Contents	<ul style="list-style-type: none"> Hotel logo Service menu Language menu Weather (required external information server) Advertising illustration Date and time 		<ul style="list-style-type: none"> Talking time IP address MAC address SIP register status Firmware version Failed network link warning Firmware upgrade via TFTP
Easy Administration	<ul style="list-style-type: none"> Web GUI Auto provisioning via TFTP 		
Codec	<ul style="list-style-type: none"> G.711 		
Network Protocol	<ul style="list-style-type: none"> HTTP server ToS / VLAN IEEE 802.1 p/q 		<ul style="list-style-type: none"> Static IP, DHCP Client
SIP	<ul style="list-style-type: none"> SIP V2 (RFC3261) 		
Security	<ul style="list-style-type: none"> Web login authentication for web setup MD5 for SIP authentication (RFC 2069/ RFC2617) 		<ul style="list-style-type: none"> HTTPS TLS 1.2
DTMF	<ul style="list-style-type: none"> In-Band / Out-of-Band DTMF(RFC2833) / SIP Info (RFC2976) 		
Voice Quality	<ul style="list-style-type: none"> Echo canceller: LEC / AEC CNG: Comfortable noise generator 		<ul style="list-style-type: none"> Jitter buffer/PLC
Tones	<ul style="list-style-type: none"> Ring back tone (local), Busy tone, Dial tone 		

2. Hardware Specifications

Display	<ul style="list-style-type: none"> Type 4.3" resistive touch WQVGA color TFT with backlight Resolution 272 x 480 pixels Display size W x H 55.5mm x 96.7mm
LED Indications	<ul style="list-style-type: none"> Line keys(red), HOLD(red)/MUTE(red), SPEAKER(red), and MESSAGE(red) keys
Power	<ul style="list-style-type: none"> PoE : IEEE 802.3af AC adaptor: Input: 100 ~ 240 VAC, Output: 5V / 1.5A (optional)
Jacks	<ul style="list-style-type: none"> RJ45 10/100 Mbs: LAN port x 1, PC port x1; DC jack x 1, RJ9 Handset jack x 1
Ethernet cable	<ul style="list-style-type: none"> 9 feet x 1
Size and Weight	<ul style="list-style-type: none"> Dimensions: 201mm(L) x132mm(W) x 121mm(H), Weight: 592g (Low profile) Dimensions: 201mm(L) x132mm(W) x 156mm(H), Weight: 600g (High profile)

3. Regulatory

	USA	EU	
EMI	FCC Part 15B	EN55032	
Safety		EN 60950-1	
EMC		EN 55024	EC 61000-4-4
		EN 61000-3-2	EC 61000-4-5
		EN 61000-3-3	EC 61000-4-6
		IEC 61000-4-2	EC 61000-4-8
		IEC 61000-4-3	EC 61000-4-11
RoHS	<ul style="list-style-type: none"> Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC) 		
Temperature	<ul style="list-style-type: none"> Storage: Low temperature at -10°C Operating Low temperature at 0°C 	<ul style="list-style-type: none"> High temperature at +60°C High temperature at +40°C 	

Model:

VM-9100-SLT-99(S)

VM-9200-SLT-99(S)

