


VX-8108-SMB(A)

VX-8208-SMB(A)

1- or 2- Line Cordless
Analog DECT Master Phone



VX-8108-SMB(A)



VX-8208-SMB(A)

- Full duplex speakerphone.
- Message waiting indicator.
- Pair up to 4 cordless remotes.
- Customizable hotel logo and service dials.
- Up to 7 on-screen scrolling guest service icons.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



1. Features

Handset

	8208	8108
Keys	- Dial keys (0~9, *, #) - Line keys Line1, Line2, END - Hard keys EMERGENCY, GUEST SERVICES, MESSAGE - Function keys Info, VOLUME +/-, HOLD, and 3 soft keys	(0~9, *, #) - Line, END - EMERGENCY, GUEST SERVICES, MESSAGE - Info, VOLUME +/-, MUTE, and 3 soft keys
Phone Features	- Up to 7 on-screen scrolling guest service icons - Full duplex speaker phone - Call hold and resume (8200) - Handset, speaker, and ringer volume control	3 programmable hard keys - Mute and unmute (8100) - Red color message waiting indicator for ringing and message waiting
Display Contents	- Main logo - Service dial list/icons - Battery status: power level, charging status	- DECT signal status - Line status - Firmware version
DECT Standard	- DECT / CAT iq2.0 compatible - Radio Frequency Range : 1880~1930 MHz - EU : 1881.792(ch0)~1897.344(ch9) 10 channels - US : 1921.536(ch0)~1928.448(ch4) 5 channels - JP : 1895.616(ch0)~1902.528(ch4) 5 channels	- Channel Space : 1728 KHz - Bit rate : 1150 Kbit/s - Modulation : GFSK - Voice coding : 16 Kbit/s - RF power : 7 dBm

Base

DECT Standard	- DECT / CAT iq2.0 compatible - Radio Frequency Range : 1880~1930 MHz - EU : 1881.792(ch0)~1897.344(ch9) 10 channels - US : 1921.536(ch0)~1928.448(ch4) 5 channels - JP : 1895.616(ch0)~1902.528(ch4) 5 channels	- Channel Space : 1728 KHz - Bit rate : 1150 Kbit/s - Modulation : GFSK - Voice coding : 16 Kbit/s - RF power : 17 dBm
---------------	--	--

	8208-SMB-BB(A)	8108-SMB-BB(A)	8208-SMB(A)	8108-SMB(A)
Battery Backup	Y	Y	N	N

2. Hardware Specifications

Handset

Display	• 2.0" TFT color display	
LED Indications	• Message waiting indicator and keypad backlight	
Power	• 3.7v / 900mAh Li-ion battery	• Standby time: 240hrs
	• Charging time: 5hrs	• Talking time: 9hrs
Contact pins	• 3 contact pins for charging and hook detecting	
Size and Weight	• Dimensions: 190mm(L) x 50mm(W) x 16.5mm mm(H), Weight: 140g(battery included)	

Base

Key	• Find handset key to quick locate all handsets	
Power	• AC adaptor: Input: 100 ~ 240 VAC, Output: 5.9V / 1A	
	• Optional battery backup while power failure	
Jacks	• RJ14 PSTN jack x 1, DC jack x 1, Reset x 1	
Contact pins	• 3 contact pins for charging and hook detecting	
Line cord	• 6 feet x 1	
Battery backup	• Power failure backup battery 3.7v / 900mAh Li-ion (Optional)	
	• Charging time: 5hrs	
	• Supply standby time: 4hrs	
	• Supply talking time: 2hrs	
Size and weight	• Dimensions:115.7mm(L) x104.5mm(W) x 98.8mm(H), Weight: 340g(Base only)	
	• Dimensions:115.7mm(L) x104.5mm(W) x 190mm(H), Weight: 480g(Handset and base)	

3. Regulatory

	USA	EU
RF	FCC Part 15D	EN 301406
EMI	FCC Part 15B	EN 300386
SAR		EN 62479
Safety		EN 62368-1
EMC		EN 301489-1/-6
PSTN	TIA/EIA 968-B compliant	
RoHS	Comply with directive 2011/65/EU	
Temperature	• Storage: Low temperature at -10°C	High temperature at +60°C
	• Operating Low temperature at +5°C	High temperature at +35°C

Model:

VX-8108-SMB(A)

VX-8208-SMB(A)

VX-8108-SMB-BB(A)

VX-8208-SMB-BB(A)

VX-8108-SMB-N2(A)

VX-8208-SMB-N2(A)

VX-8108-SMB-BB-N2(A)

VX-8208-SMB-BB-N2(A)

