AEi COMMUNICATIONS

Serving the Hospitality Industry with Advanced **IP and Analog** Telephony Solutions **Worldwide**

VX-8106-SPB
VX-8206-SPB

1- or 2- Line Cordless Handset Phone

VX-8106-SPB

VX-8206-SPB

- Full duplex speakerphone.
- Message waiting indicator.
- Customizable hotel logo and service dials.
- Up to 7 on-screen scrolling guest service icons.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality,impeccable workmanship and stylish products.

At AEi your satisfaction is our priority.

www.aeicommunication.com

www.aeicommunications.com
support@aeicommunications.com

Serving the Hospitality Industry with Advanced IP and Analog Telephony Solutions Worldwide

1. Features

Handset

		8208	8108
Keys	Dial keys	(0~9, *, #)	(0~9, *, #)
	Line keys	Line1, Line2, END	Line, END
	Function keys	SPEAKER, VOLUME +/-, HOLD, MESSAGE, GUEST SERVICES, EMERGENCY, and 3 soft keys	SPEAKER, VOLUME +/-, MUTE, MESSAGE, GUEST SERVICES, EMERGENCY, and 3 soft keys

Phone Features

- One or Two Lines
- 3 hard key and 7 scrollable service dials
- Call Hold and resume (8208)
- Handset, Speaker, and Ringer volume control
- Full duplex speaker phone
- Mute and unmute (8108)
- Red color message waiting indicator for ringing and message waiting

Display Contents

- Main logo
- Service dial list/icons
- Battery status: power level, charging status
- DECT signal status
- Line status
- Firmware Version

DECT Standard

- DECT / CAT iq2.0 compatible
- Radio Frequency Range：1880~1930 MHz
- EU：1881.792(ch0)~1897.344(ch9) 10Channels
- US：1921.536(ch0)~1928.448(ch4) 5 Channels
- JP：1895.616(ch0)~1902.528(ch4) 5 Channels
- Channel Space：1728 KHz
- Bit rate：1150 Kbit/s
- Modulation：GFSK
- Voice coding：16 Kbit/s
- RF power：7 dBm

2. Hardware Specifications

Handset

Display	2.0“ TFT color display
LED Indications	Message waiting indicator
Power	3.7v / 900 mAh Li-ion battery Charging Time: 5 hrs Standby Time: 240 hrs Talking Time: 9 hrs
Contact pins	3 contact pins for charging and hook detecting
Size and Weight	Dimensions: 190mm(L) x 50mm(W) x 16.5mm mm(H), Weight: 140g(battery included)

Base

Power	AC adaptor: Input: 100 ~ 240 VAC, Output: 5.9V / 1A
Jacks	DC jack x 1
Contact pins	3 contact pins for charging
Size and Weight	Dimensions:115.7mm(L) x104.5mm(W) x 98.8mm(H), Weight: 340g(Base only) Dimensions:115.7mm(L) x104.5mm(W) x 190mm(H), Weight: 480g(Handset and base)

3. Regulatory

	USA	EU
RF	FCC Part 15D	EN 301406
EMI	FCC Part 15B	EN 300386
SAR		EN 62479
Safety		EN 60368-1
EMC		EN 301489-1/6
RoHS	Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)	
Temperature	Storage: Low temperature at -10°C	High temperature at +60°C
	Operating Low temperature at +5°C	High temperature at +35°C

Model:

VX-8108-SPB

VX-8208-SPB

Specifications are subject to change without notice.
Design Patent Pending©2018 AEI Communications. All rights reserved.