

AGR-6106-S

Single line  
Analog phone

AGR-6109-S



- Single line analog phone.
- Hearing aid support
- Full duplex speakerphone.
- Message waiting indicator.
- 6 or 9 customizable service dials.
- Faceplate with customizable hotel logo.

**AEI** brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEI** your satisfaction is our priority.



## 1. Features

- |                |   |
|----------------|---|
| Keys           | <ul style="list-style-type: none"> <li>• Dial keys (0~9, *, #)</li> <li>• Line keys N/A</li> <li>• Function keys Speaker, Volume up/down, 6 or 9 programmable service keys</li> </ul>   |
| Phone Features | <ul style="list-style-type: none"> <li>• Single line telephone system with speakerphone</li> <li>• Adjustable High-low ringer (2 way selectable switch)</li> <li>• 8 steps speakerphone digital volume control</li> <li>• 4 steps handset digital volume control</li> <li>• 6 non volatile one-touch programmable speed dial memory button</li> <li>• Tone dialing only</li> <li>• Hearing Aid Receiver Compliant</li> <li>• PBX / Standard Line compatible</li> <li>• Multi Purpose LED indicator for Message Waiting and Incoming Ring</li> </ul> |

## 2. Hardware Specifications

- |                 |  |
|-----------------|--|
| Power           | • Line Power (without AC adaptor or battery)               |
| Jacks           | • RJ11 PSTN jack x 1                                       |
| Size and Weight | • Dimensions: 191mm(L) x 110mm(W) x 106mm(H), Weight: 576g |

## 3. Regulatory

	USA	EU
PSTN	Part 68	TBR 21
EMI	FCC Part 15B	EN55032 & EN55024 EN60950-1
RoHS	• Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)	
Telecom	• TIA/EIA 968-B compliant	
Temperature	• Storage: Low temperature at -10°C	High temperature at +60°C
	• Operating Low temperature at +5°C	High temperature at +35°C

**Model:**  
**AGR-6106-S**  
**AGR-6109-S**

