

AGR-9106-SM

AGR-9206-SM

1- or 2- Line Coded  
Analog DECT Master Phone



**AGR-9106-SM**



**AGR-9206-SM**

- Message waiting indicator.
- Full duplex speakerphone.
- Pair up to 4 cordless remotes.
- Faceplate with customizable hotel logo.
- Up to 6 customizable guest service keys.

**AEi** brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



## 1. Features

	Keys	9206	9106
		<ul style="list-style-type: none"> <li>Dial keys (0~9, *, #)</li> <li>Line keys Line1, Line2, END</li> <li>Function keys HOLD, SPEAKER, VOLUME, 6 guest service keys</li> </ul>	<ul style="list-style-type: none"> <li>(0~9, *, #)</li> <li>Line, END</li> <li>MUTE, SPEAKER, VOLUME, 6 guest service keys</li> </ul>
Phone Features		<ul style="list-style-type: none"> <li>Up to 6 programmable guest service keys</li> <li>Call hold and resume (9206)</li> <li>Red color message waiting indicator for ringing and message waiting</li> </ul>	<ul style="list-style-type: none"> <li>Full duplex speaker phone</li> <li>Mute and unmute (9106)</li> <li>Handset, speaker and ringer volume control</li> </ul>
DECT Standard		<ul style="list-style-type: none"> <li>DECT / CAT iq 2.0 compatible</li> <li>Radio Frequency Range : 1880~1930 MHz</li> <li>EU : 1881.792(ch0)~1897.344(ch9) 10 channels</li> <li>US : 1921.536(ch0)~1928.448(ch4) 5 channels</li> <li>JP : 1895.616(ch0)~1902.528(ch4) 5 channels</li> </ul>	<ul style="list-style-type: none"> <li>Channel Space : 1728 KHz</li> <li>Bit rate : 1150 Kbit/s</li> <li>Modulation : GFSK</li> <li>Voice coding : 16 Kbit/s</li> <li>RF power : 17 dBm</li> </ul>

## 2. Hardware Specifications

LED Indications	<ul style="list-style-type: none"> <li>Line keys, HOLD/MUTE, SPEAKER keys, message waiting</li> </ul>
Power	<ul style="list-style-type: none"> <li>AC adaptor: Input: 100 ~ 240 VAC, Output: 5.9V / 1A</li> </ul>
Jacks	<ul style="list-style-type: none"> <li>RJ14(RJ11) PSTN jack x 1, DC jack x 1</li> </ul>
Line cord	<ul style="list-style-type: none"> <li>6 feet x 1</li> </ul>
Size and Weight	<ul style="list-style-type: none"> <li>Dimensions:193mm(L) x109mm(W) x 105mm(H), Weight: 595g</li> </ul>

## 3. Regulatory

	USA	EU
RF	FCC Part 15D	EN 301406
EMI	FCC Part 15B	EN 300386
SAR		EN 62479
Safety		EN 60950-1
EMC		EN 301489-1/6
PSTN	TIA/EIA 968-B compliant	
RoHS	Comply with directive 2011/65/EU	
Temperature	<ul style="list-style-type: none"> <li>Storage: Low temperature at -10°C</li> <li>Operating: Low temperature at +5°C</li> </ul>	<ul style="list-style-type: none"> <li>High temperature at +60°C</li> <li>High temperature at +35°C</li> </ul>

### Model:

AGR-9106-SM

AGR-9206-SM

