

MP-5102(A) | Single Line  
Analog phone



- Basic single-line corded analog phone
- Fix ringer sound level
- Faceplate with customizable hotel logo
- 2 non volatile one-touch programmable speed dial buttons

**AEi** brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



## 1. Features

- |                |   |
|----------------|---|
| Keys           | <ul style="list-style-type: none"> <li>• Dial keys (0~9, *, #)</li> <li>• Function keys 2 speed dial keys</li> </ul>  |
| Phone Features | <ul style="list-style-type: none"> <li>• Basic single line telephone system</li> <li>• Fix ringer sound level</li> <li>• One adjustable volume switch "normal, high" to select the handset receiving volume level</li> <li>• 2 non volatile one-touch programmable speed dial buttons</li> <li>• Tone dialing only</li> <li>• Hearing aid receiver compliant PBX/ Standard line compatible</li> </ul> |

## 2. Hardware Specifications

- |                 |   |
|-----------------|---|
| Power           | • Telephone line powered (without AC adaptor or battery)  |
| Ring Voltage    | • 40V RMS minimum   |
| Jacks           | • RJ11 PSTN jack x 1, RJ9 Handset jack x 1                |
| Line cord       | • 10 feet x 1   |
| Size and Weight | • Dimensions:220mm(L) x150mm(W) x 120mm(H), Weight: 1160g |

## 3. Regulatory

	USA	EU
PSTN	Part 68	TBR 21
EMI	FCC Part 15B	EN55032 & EN55024 EN62368-1
RoHS	• Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)	
Telecom	• TIA/EIA 968-B compliant	
Temperature	• Storage: Low temperature at -10°C	High temperature at +60°C
	• Operating Low temperature at +5°C	High temperature at +35°C

**Model:**  
**MP-5102**

