

## Serving the Hospitality Industry with Advanced IP and Analog Telephony Solutions Worldwide

MP-5102(A)

Single Line Classic

Analog Phone

- Retro classic design.
- Fix ringer sound level.
- Faceplate with customizable hotel logo.
- 2 non-volatile one-touch programmable guest service keys.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.





## www.aeicommunications.com support@aeicommunications.com

## 1. Features

<ul> <li>Dial keys</li> </ul>	(0~9, *, #)	
Function keys		eys
Phone Features   Basic single line telephone system		
Fix ringer sound I	evel	
One adjustable v	olume switch "normal, high	" to select the handset receiving volume level
• 2 non-volatile one	e-touch programmable spe	ed dial buttons
• Tone dialing only		
Hearing aid recei	ver compliant PBX/ Standa	ard line compatible
· ·	·	
ifications		
Telephone line po	Telephone line powered (without AC adaptor or battery)	
• 40V RMS minimu	40V RMS minimum	
RJ11 PSTN jack:	RJ11 PSTN jack x 1, RJ9 Handset jack x 1	
• 10 feet x 1	10 feet x 1	
Dimensions:220n	Dimensions:220mm(L) x150mm(W) x 120mm(H), Weight: 1160g	
	USA	EU
FCC		EN55032 & EN55035
		EN62368-1
TIA/EIA 96	68-B compliant	
	Comply with directive 20	11/65/EU
Storage: Low	temperature at -10°C	High temperature at +60°C
Operating: Low		High temperature at +35°C
	<ul> <li>Function keys</li> <li>Basic single line for the second of the second</li></ul>	<ul> <li>Function keys M1, M2 guest service key</li> <li>Basic single line telephone system</li> <li>Fix ringer sound level</li> <li>One adjustable volume switch "normal, high</li> <li>2 non-volatile one-touch programmable spece</li> <li>Tone dialing only</li> <li>Hearing aid receiver compliant PBX/ Standations</li> <li>Telephone line powered (without AC adaptor 40V RMS minimum</li> <li>RJ11 PSTN jack x 1, RJ9 Handset jack x 1</li> <li>10 feet x 1</li> <li>Dimensions:220mm(L) x150mm(W) x 120m</li> <li>USA</li> <li>TIA/EIA 968-B compliant Comply with directive 20</li> <li>Storage: Low temperature at -10°C</li> </ul>

Model: MP-5102(A) MP-5102(A)-N



Specifications are subject to change without notice. Design Patent Pending©2023 AEI Communications. All rights reserved.