

MP-5102(A)

Single Line Classic
Analog Phone



- Retro classic design.
- Fix ringer sound level.
- Faceplate with customizable hotel logo.
- 2 non-volatile one-touch programmable guest service keys.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



1. Features

- | | |
|----------------|--|
| Keys | <ul style="list-style-type: none">• Dial keys (0~9, *, #)• Function keys M1, M2 guest service keys |
| Phone Features | <ul style="list-style-type: none">• Basic single line telephone system• Fix ringer sound level• One adjustable volume switch “normal, high” to select the handset receiving volume level• 2 non-volatile one-touch programmable speed dial buttons• Tone dialing only• Hearing aid receiver compliant PBX/ Standard line compatible |

2. Hardware Specifications

- | | |
|-----------------|---|
| Power | <ul style="list-style-type: none">• Telephone line powered (without AC adaptor or battery) |
| Ring Voltage | <ul style="list-style-type: none">• 40V RMS minimum |
| Jacks | <ul style="list-style-type: none">• RJ11 PSTN jack x 1, RJ9 Handset jack x 1 |
| Line cord | <ul style="list-style-type: none">• 6 feet x 1 |
| Size and Weight | <ul style="list-style-type: none">• Dimensions:220mm(L) x150mm(W) x 120mm(H), Weight: 1160g |

3. Regulatory

- | | USA | EU |
|-------------|--|---|
| EMC | FCC Part 15B | EN55032 & EN55035
EN62368-1 |
| PSTN | TIA/EIA 968-B compliant | |
| RoHS | Comply with directive 2011/65/EU | |
| Temperature | <ul style="list-style-type: none">• Storage: Low temperature at -10°C• Operating: Low temperature at +5°C | <ul style="list-style-type: none">• High temperature at +60°C• High temperature at +35°C |

Model:
MP-5102(A)
MP-5102(A)-N

