

VM-9108-S(S)

VM-9208-S(S)

1 or 2 Lines
SIP Phone



- 1 or 2 lines SIP phone.
- Magnetic hook switch.
- Full duplex speakerphone.
- 8 customizable service dials.
- Message waiting key with indicator.
- Faceplate with customizable hotel logo.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



1. Features

Keys	9208	9108
	<ul style="list-style-type: none"> • Dial keys (0~9, *, #) • Line keys Line1, Line2 with red color LED • Function keys REDIAL, SPEKAER, VOLUME +/-, HOLD, MESSAGE, 8 Service dial keys 	<ul style="list-style-type: none"> • (0~9, *, #) • NA • REDIAL, SPEKAER, VOLUME +/-, MUTE , MESSAGE, 8 Service dial keys
Phone Features	<ul style="list-style-type: none"> • 8 customizable service dials • Call Hold and resume(9208 only) • Handset, speaker and ringer volume control • Redial last call 	<ul style="list-style-type: none"> • Mute and resume(9108 only) • Red color message key with indicator • Ringing indicator • Full duplex speaker phone
Display Contents	<ul style="list-style-type: none"> • Talking time • IP Address • MAC Address • Clock 	<ul style="list-style-type: none"> • SIP Register Status • Firmware Version • Failed Network link Warning
Easy Administration	<ul style="list-style-type: none"> • Web GUI • Auto provisioning via TFTP 	<ul style="list-style-type: none"> • Firmware upgrade via TFTP
Codec	<ul style="list-style-type: none"> • G.711 	
Network Protocol	<ul style="list-style-type: none"> • HTTP server • ToS / VLAN IEEE 802.1 p/q 	<ul style="list-style-type: none"> • Static IP, DHCP Client
SIP	<ul style="list-style-type: none"> • SIP V2 (RFC3261) 	
Security	<ul style="list-style-type: none"> • Web login authentication for web setup • MD5 for SIP authentication (RFC 2069/ RFC2617) 	<ul style="list-style-type: none"> • HTTPS • TLS 1.2
DTMF	<ul style="list-style-type: none"> • In-Band / Out-of-Band DTMF(RFC2833) / SIP Info (RFC2976) 	
Voice Quality	<ul style="list-style-type: none"> • CNG: Comfortable noise generator • Echo canceller: LEC / AEC • Jitter buffer/PLC 	
Tones	<ul style="list-style-type: none"> • Ring back tone (local), Busy tone, Dial tone 	

2. Hardware Specifications

- | | |
|-----------------|---|
| Display | • Dot matrix LCM 16 x 2 with backlight |
| LED Indications | • Line keys(red), HOLD(red)/MUTE(red), SPEAKER(red), and MESSAGE(red) keys |
| Power | • PoE : IEEE 802.3af
• AC adaptor: Input: 100 ~ 240 VAC, Output: 5V / 1.5A (optional) |
| Jacks | • RJ45 10/100 Mbs: LAN port x 1, PC port x1; DC jack x 1, RJ9 Handset jack x 1 |
| Ethernet cable | • 9 feet x 1 |
| Size and Weight | • Dimensions: 201mm(L) x132mm(W) x 121mm(H), Weight: 620g (Low profile)
• Dimensions: 201mm(L) x132mm(W) x 156mm(H), Weight: 625g (High profile) |

3. Regulatory

	USA	EU	
EMI	FCC Part 15B	EN55032	
Safety		EN 60950-1	
EMC		EN55024	EC61000-4-4
		EN61000-3-2	EC61000-4-5
		EN61000-3-3	EC61000-4-6
		IEC61000-4-2	EC61000-4-8
		IEC61000-4-3	EC61000-4-11
RoHS	• Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)		
Temperature	• Storage: Low temperature at -10°C	High temperature at +60°C	
	• Operating Low temperature at 0°C	High temperature at +40°C	

Model:

VM-9108-S-99(S)

VM-9208-S-99(S)

