

Serving the Hospitality Industry with Advanced IP and Analog Telephony Solutions Worldwide

> AGR-6106-S S AGR-6109-S

Single line Analog phone

- Hearing aid support.
- Handsfree speakerphone.
- Message waiting indicator.
- 6 or 9 customizable service dials.
- Faceplate with customizable hotel logo.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At AEi your satisfaction is our priority.





1. Features

AEi Corporate Office Carrollton, Texas, U.S.A Sales: +1.254.3350555 sales@aeicommunications.com

**AEi EMEA Office** London, United Kingdom Sales: +44 (0)7557.645276 emea@aeicommunications.com

**AEi Asia Pacific Office** New Taipei City, Taiwan Sales: +886.2.26968809 asiapac@aeicommunications.com

## **AEi Middle East Office**

Dubai, United Arab Emirates Sales: +971.553648916 Emea@aeicommunications.com

## AEi Corporate Office Penang, Malaysia Sales: +604.3994341

so.asia@aeicommunications.com

## AEi CEE&CIS Office

Budva, Montenegro Sales: +382 69 891 251 eastern.europe@aeicommunications.com

| Keys                           | <ul> <li>Dial keys</li> </ul>  | (0~9, *, #)                           |   |  |
|--------------------------------|--|---------------------------------------|---|--|
|                                | Line keys  | N/A                                   |   |  |
|                                | Function keys  | Speaker, Volume up/d                  | lown, 6 or 9 programmable service keys    |  |
| Phone Features                 | Single line telephone system with speakerphone                                 |                                       |   |  |
|                                | Adjustable High-low ringer (2-way selectable switch)                           |                                       |   |  |
|                                | 8 steps speakerphone digital volume control                                    |                                       |   |  |
|                                | 4 steps handset digital volume control   |                                       |   |  |
|                                | 6 non volatile one-touch programmable speed dial memory button                 |                                       |   |  |
|                                | Tone dialing only  |                                       |   |  |
|                                | Hearing Aid Receiver Compliant   |                                       |   |  |
|                                | PBX / Standard Line compatible   |                                       |   |  |
|                                | Multi Purpose LED indicator for Message Waiting and Incoming Ring              |                                       |   |  |
| Power                          | Line Power (without AC adaptor or battery)                                     |                                       |   |  |
| Ring Voltage • 40V RMS minimum |  |                                       |   |  |
| Jacks                          |  |                                       |   |  |
| Size and Weight                | <ul> <li>Dimensions: 191mm(L) x 110mm(W) x 106mm(H), Weight: 576g</li> </ul>   |                                       |   |  |
|                                |  |                                       |   |  |
| Regulatory ເ                   |  | USA                                   | EU  |  |
| EMC                            | FCC  | Part 15B                              | EN55032 & EN55035<br>EN62368-1            |  |
| RoHS •                         | Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/ |                                       | amended by commission decision 2005/613/E |  |
| Telecom •                      | TIA/EIA 968-B compliant  |                                       |   |  |
| Temperature •                  |  |                                       | High temperature at +60°C                 |  |
| •                              | Operating Low ter  | nperature at +5°C                     | High temperature at +35°C                 |  |
|                                |  | · · · · · · · · · · · · · · · · · · · |   |  |

Model: AGR-6106-S AGR-6109-S

RoHS

Specifications are subject to change without notice. Design Patent Pending©2018 AEI Communications. All rights reserved.

FC CE