

Serving the Hospitality Industry with Advanced IP and Analog Telephony Solutions Worldwide

VH-6108-S(A)

Single Line

Analog Phone

- Single line analog phone.
- Hearing aid support.
- Magnetic hook switch.
- Full duplex speakerphone.
- 8 customizable service dials.
- Message waiting indicator.
- Faceplate with customizable hotel logo.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At AEi your satisfaction is our priority.





AEi-Corporate Office Carrollton, Texas, U.S.A Sales: +1.254.3350555 sales@aeicommunications.com

AEi-EMEA Office London, United Kingdom Sales: +44 (0)1753.643736 emea@aeicommunications.com

AEi-Asia Pacific Office New Taipei City, Taiwan Sales: +886.2.26968809

asiapac@aeicommunications.com

AEi-CEE&CIS Office

Budva, Montenegro Sales: +382 69 891 251 eastern.europe@aeicommunications.com

AEi-Corporate Office Penang, Malaysia Sales: +604.3994341 so.asia@aeicommunications.com

Keys	• Dial keys (0~9, *, #)	
	• Function keys Volume up/down, Mute, Redial, N	Message and Guest Service Keys x 8
Phone Features	 Single line telephone system with speakerphone Adjustable High-low ringer (2 way selectable switch) 7 steps speakerphone digital volume control 8 programmable Guest Service Keys and 1 programmable message key 4 steps handset digital volume control 	 Multi Purpose LED indicator for Message Waiting and Incoming Ring Last number redial (Max up to 31 digitals) Microphone Mute with LED indicator Hearing Aid Receiver Compatible PBX / Standard Line compatible Tone dialing only
2. Hardware Sp	adiliantiana	
LED Indications	Message waiting indicator	
LED Indications Power Ring Voltage	Message waiting indicator	6.5
LED Indications Power Ring Voltage Jacks	 Message waiting indicator Telephone line powered 40V RMS minimum RJ11 Jack x 1, RJ9 jack x 1. 	
LED Indications Power Ring Voltage Jacks Line cord	 Message waiting indicator Telephone line powered 40V RMS minimum RJ11 Jack x 1, RJ9 jack x 1. 10 feet x 1 	
LED Indications Power Ring Voltage Jacks	 Message waiting indicator Telephone line powered 40V RMS minimum RJ11 Jack x 1, RJ9 jack x 1. 	, Weight: 630g
LED Indications Power Ring Voltage Jacks Line cord	 Message waiting indicator Telephone line powered 40V RMS minimum RJ11 Jack x 1, RJ9 jack x 1. 10 feet x 1 	, Weight: 630g EU
LED Indications Power Ring Voltage Jacks Line cord Size and Weight	 Message waiting indicator Telephone line powered 40V RMS minimum RJ11 Jack x 1, RJ9 jack x 1. 10 feet x 1 Dimensions: 132mm(L) x 208mm(W) x 70mm(H) 	
LED Indications Power Ring Voltage Jacks Line cord Size and Weight 3. Regulatory	 Message waiting indicator Telephone line powered 40V RMS minimum RJ11 Jack x 1, RJ9 jack x 1. 10 feet x 1 Dimensions: 132mm(L) x 208mm(W) x 70mm(H) USA 	
LED Indications Power Ring Voltage Jacks Line cord Size and Weight 3. Regulatory PSTN	 Message waiting indicator Telephone line powered 40V RMS minimum RJ11 Jack x 1, RJ9 jack x 1. 10 feet x 1 Dimensions: 132mm(L) x 208mm(W) x 70mm(H) USA FCC Part 68 	EU EN55032 & EN55024 EN60950-1
LED Indications Power Ring Voltage Jacks Line cord Size and Weight 3. Regulatory PSTN EMC	 Message waiting indicator Telephone line powered 40V RMS minimum RJ11 Jack x 1, RJ9 jack x 1. 10 feet x 1 Dimensions: 132mm(L) x 208mm(W) x 70mm(H) USA FCC Part 68 FCC Part 15B 	EU EN55032 & EN55024 EN60950-1
LED Indications Power Ring Voltage Jacks Line cord Size and Weight 3. Regulatory PSTN EMC RoHS	 Message waiting indicator Telephone line powered 40V RMS minimum RJ11 Jack x 1, RJ9 jack x 1. 10 feet x 1 Dimensions: 132mm(L) x 208mm(W) x 70mm(H) USA FCC Part 68 FCC Part 15B Comply with directive 2002/95/EC RoHS (as amen 	EU EN55032 & EN55024 EN60950-1

Model: VH-6108-S(A)



Serving the Hospitality Industry with Advanced IP and Analog Telephony Solutions Worldwide

Specifications are subject to change without notice. Design Patent Pending©2018 AEI Communications. All rights reserved.