

VH-6108-S(A)

Single Line
Analog Phone



- Hearing aid support.
- Magnetic hook switch.
- Handsfree speakerphone.
- 8 customizable service dials.
- Message waiting indicator.
- Faceplate with customizable hotel logo.

AEI brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEI** your satisfaction is our priority.



1. Features

Keys	<ul style="list-style-type: none"> • Dial keys (0~9, *, #) • Function keys Volume up/down, Mute, Redial, Message and Guest Service Keys x 8
Phone Features	<ul style="list-style-type: none"> • Single line telephone system with speakerphone • Adjustable High-low ringer (2-way selectable switch) • 7 steps speakerphone digital volume control • 8 programmable Guest Service Keys and 1 programmable message key • 4 steps handset digital volume control • Multi Purpose LED indicator for Message Waiting and Incoming Ring • Last number redial (Max up to 31 digits) • Microphone Mute with LED indicator • Hearing Aid Receiver Compatible • PBX / Standard Line compatible • Tone dialing only

2. Hardware Specifications

LED Indications	<ul style="list-style-type: none"> • MUTE (red), SPEAKER (red), and Message waiting indicator
Power	<ul style="list-style-type: none"> • Telephone line powered
Ring Voltage	<ul style="list-style-type: none"> • 40V RMS minimum
Jacks	<ul style="list-style-type: none"> • RJ11 Jack x 1, RJ9 jack x 1.
Line cord	<ul style="list-style-type: none"> • 10 feet x 1
Size and Weight	<ul style="list-style-type: none"> • Dimensions: 132mm(L) x 208mm(W) x 70mm(H), Weight: 630g

3. Regulatory

	USA	EU
EMC	FCC Part 15B	EN55032 & EN55035 EN62368-1
RoHS	<ul style="list-style-type: none"> • Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC) 	
Telecom	<ul style="list-style-type: none"> • TIA/EIA 968-B compliant 	
Temperature	<ul style="list-style-type: none"> • Storage: Low temperature at -10°C • Operating Low temperature at +5°C 	<ul style="list-style-type: none"> High temperature at +60°C High temperature at +35°C

Model:
 VH-6108-S(A)

