

VM-6108-SF(A)

Single line
Analog Phone



- Single line analog phone.
- Magnetic hook switch.
- Full duplex speakerphone.
- 8 customizable service dials.
- Message waiting indicator.
- Faceplate with customizable hotel logo.
- Support FSK Message Waiting Signal Type

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



1. Features

- | | |
|----------------|--|
| Keys | <ul style="list-style-type: none"> • Dial keys (0~9, *, #) • Function keys Redial, Speaker, Volume +/-, Mute, Message, 8 service dial keys |
| Phone Features | <ul style="list-style-type: none"> • 8 customizable service dials • Handset, speaker and ringer volume control • Red color message key with indicator • Mute and unmute • Redial last call • Ringing indicator |

2. Hardware Specifications

- | | |
|-----------------------------|--|
| LED Indications | • Line keys(red), MUTE(red), SPEAKER(red), and MESSAGE(red) keys |
| Power | • Telephone line powered |
| Jacks | • RJ14(RJ11) PSTN jack x 1, RJ9 Handset jack x 1 |
| Ring Voltage | • 40V RMS minimum |
| Line cord | • 10 feet x 1 |
| Size and Weight | • Dimensions: 201mm(L) x132mm(W) x 121mm(H), Weight: 600g |
| Message Waiting Signal Type | • FSK, High Voltage, Low Voltage, Reverse Polarity |

3. Regulatory

	USA	EU
PSTN	Part 68	TBR 21
EMC	FCC Part 15B	EN55032 & EN55024 EN62368-1
RoHS	• Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)	
Telecom	• TIA/EIA 968-B compliant	
Temperature	• Storage: Low temperature at -10°C	High temperature at +60°C
	• Operating Low temperature at +5°C	High temperature at +35°C

Model:
VM-6108-S(A)

