

VM-6108-SF(A)

Single line
Analog Phone



- Hearing aid support.
- Magnetic hook switch.
- Handsfree speakerphone.
- 8 customizable service dials.
- Message key with waiting indicator.
- Faceplate with customizable hotel logo.
- Support FSK message waiting signal type.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



1. Features

- | | |
|----------------|--|
| Keys | <ul style="list-style-type: none"> • Dial keys (0-9, *, #) • Function keys Redial, Speaker, Volume +/-, Mute, Message, 8 service dial keys |
| Phone Features | <ul style="list-style-type: none"> • Single line telephone system with speakerphone • Adjustable High-low ringer (2-way selectable switch) • 7 steps speakerphone digital volume control • 8 programmable Guest Service Keys and 1 programmable message key • 4 steps handset digital volume control • Tone dialing only • Multi-Purpose LED indicator for Message Waiting and Incoming Ring • Last number redial (Max up to 31 digitals) • Microphone Mute with LED indicator • Hearing Aid Receiver Compatible • PBX / Standard Line compatible |

2. Hardware Specifications

- | | |
|-----------------------------|---|
| LED Indications | • MUTE (red), SPEAKER (red), and MESSAGE (red) keys |
| Power | • Telephone line powered |
| Jacks | • RJ14(RJ11) PSTN jack x 1, RJ9 Handset jack x 1 |
| Ring Voltage | • 40V RMS minimum |
| Message waiting signal type | • FSK, high voltage, low voltage, reverse polarity |
| Line cord | • 10 feet x 1 |
| Size and Weight | • Dimensions: 201mm(L) x132mm(W) x 121mm(H), Weight: 600g |

3. Regulatory

	USA	EU
EMC	FCC Part 15B	EN55032 & EN55035 EN62368-1
RoHS	• Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)	
Telecom	• TIA/EIA 968-B compliant	
Temperature	• Storage: Low temperature at -10°C	High temperature at +60°C
	• Operating Low temperature at +5°C	High temperature at +35°C

Model:
VM-6108-SF(A)

