

VS-6104-S(A)

VS-6104-S(A)-EW

Single Line Analog
Speaker Phone



- Single line analog phone
- Wall mount speaker phone
- Customizable service dials
- Message key with indicator
- Faceplate with customizable hotel logo
- Optional emergency wire (white color only)

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



1. Features

| | |
|----------------|--|
| Keys | <ul style="list-style-type: none"> Dial keys (0~9, *, #) Line keys N/A Function keys Speaker, Mute, Volume UP/Down, 4 service dial keys |
| Phone Features | <ul style="list-style-type: none"> Single line telephone system with speakerphone 4 programmable service dials Tone dialing only PBX / Standard Line compatible Mute and unmute Ringer volume switch |

2. Hardware Specifications

| | |
|-----------------|--|
| LED Indications | <ul style="list-style-type: none"> MUTE(red), SPEAKER(red), MESSAGE(red) keys |
| Power | <ul style="list-style-type: none"> Line Power (without AC adaptor or battery) |
| Ring Voltage | <ul style="list-style-type: none"> 40V RMS minimum |
| Line Cord | <ul style="list-style-type: none"> 0.7 feet x 1 |
| Jacks | <ul style="list-style-type: none"> RJ11 PSTN jack x 1 |
| Emergency wire | <ul style="list-style-type: none"> 3.3 feet x 1 (white color only) |
| Size and Weight | <ul style="list-style-type: none"> Dimensions: 180mm(L) x 100mm(W) x 27.5 mm(H), Weight: 230g |

3. Regulatory

| | USA | EU |
|-------------|---|--|
| PSTN | FCC Part 68 | |
| EMI | FCC Part 15B | EN55032 & EN55024 EN60950-1 |
| RoHS | <ul style="list-style-type: none"> Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC) | |
| Temperature | <ul style="list-style-type: none"> Storage: Low temperature at -10°C Operating Low temperature at +5°C | <ul style="list-style-type: none"> High temperature at +60°C High temperature at +35°C |

Model:

VS-6104-S(A)

VS-6104-S(A)-EW

