


# Serving the Hospitality Industry with Advanced IP and Analog Telephony Solutions Worldwide

VS-6104-S(A)-EW

Single Line Analog Speaker Phone







- Wall mountable speaker phone.
- Customizable service dials.
- Message key with indicator.
- Faceplate with customizable hotel logo.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At AEi your satisfaction is our priority.





# **AEi- Corporate Office**

Millbrae, California U.S.A Sales: +1.650.552.9416 sales@aeicommunications.com

#### AEi- CALA Office

Lima, Peru Sales : +51.9.8257.6251 cala@aeicommunications.com

## AEi- Asia Pacific Office

New Taipei City, Taiwan Sales : +886.2.2696.8809 asiapac@aeicommunications.com

#### AEi- EMEA Office

London, United Kingdom Sales : +44 (0)1753.643736 emea@aeicommunications.com

## AEi- Southern Asia Office

Penang, Malaysia Sales:+604.3994341 so.asia@aeicommunications.com

### AEi- CEE&CIS Office

Budva, Montenegro Sales: +382 69 891 251 eastern.europe@aeicommunications.com

# 1. Features

Keys • Dial keys (0~9, \*, #)

Line keys N/A

Function keys Speaker, Mute, Volume UP/Down, 4 service dial keys

Phone Features • :

Single line telephone system with speakerphone

4 programmable service dials

Tone dialing only

• PBX / Standard Line compatible

Mute and Resume

• Ringer volume switch

Emergency wire with button

# 2. Hardware Specifications

LED Indications • MUTE(red), SPEAKER(red), MESSAGE(red) keys

Power • Line Power (without AC adaptor or battery)

Ring Voltage • 40V RMS minimum

Line Cord • 0.7 feet x 1

Jacks • RJ11 PSTN jack x 1

Emergency Wire • Emergency cord with button, 3.3 feet x 1

Size and Weight 

Dimensions: 180mm(L) x 100mm(W) x 27.5 mm(H), Weight: 228g

3. Regulatory USA EU

PSTN Part 68 TBR 21

EMI FCC Part 15B EN55032 & EN55024

RoHS • Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)

Temperature • Storage: Low temperature at -10 °C High temperature at +60 °C

Operating Low temperature at 0 °C
 High temperature at +40 °C

Model:

VS-6104-S(A)





