

Serving the Hospitality Industry with Advanced IP and Analog Telephony Solutions Worldwide

VS-6104-S(A)

Single Line Analog Speaker Phone



·\$

З

6



• Single line analog phone.

- Wall mountable speaker phone.
- Customizable service dials.
- Message key with indicator.
- Faceplate with customizable hotel logo.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

1

З

6

9

At AEi your satisfaction is our priority.





## AEi- Corporate Office

Millbrae, California U.S.A Sales : +1.650.552.9416 sales@aeicommunications.com

AEi- CALA Office

•

Keys

**Phone Features** 

Lima, Peru Sales : +51.9.8257.6251 cala@aeicommunications.com

Dial keys

Line keys

Function keys

Tone dialing only

AEi- Asia Pacific Office New Taipei City, Taiwan Sales : +886.2.2696.8809 asiapac@aeicommunications.com

## AEi- EMEA Office

(0~9, \*, #)

Single line telephone system with speakerphone

N/A

London, United Kingdom Sales : +44 (0)1753.643736 emea@aeicommunications.com

Speaker, Mute, Volume UP/Down, 4 service dial keys

## AEi- Southern Asia Office Penang, Malaysia Sales : +604.3994341 so.asia@aeicommunications.com

## AEi- CEE&CIS Office

Budva, Montenegro Sales : +382 69 891 251 eastern.europe@aeicommunications.com

1. Features

	i i i i i i i i i i i i i i i i i i i			
	<ul> <li>PBX / Standard Line compatible</li> </ul>			
	Mute and Resume			
	Ringer volume switch			
2. Hardware Spec	cifications			
LED Indications	• MUTE(red), SPEAKER(red), MES	SAGE(red) keys		
Power	• Line Power (without AC adaptor or	battery)		
Ring Voltage	40V RMS minimum			
Line cord	• 0.7 feet x 1			
Jacks	RJ11 PSTN jack x 1			
Size and Weight	Size and Weight • Dimensions: 180mm(L) x 100mm(W) x 27.5 mm(H), Weight: 228g			
3. Regulatory	USA	EU		
PSTN	Part 68	TBR 21		

PSIN		Part 66	IDR 21
EMI		FCC Part 15B	EN55032 & EN55024
RoHS	•	Comply with directive 2002/95/EC RoHS (as amende	ed by commission decision 2005/613/EC)

Temperature

.

Storage: Low temperature at -10 ℃ Operating Low temperature at 0 ℃ High temperature at +60 °C High temperature at +40 °C

Model: VS-6104-S(A)



Specifications are subject to change without notice. Design Patent Pending© 2018 AEI Communications. All rights reserved.