

VS-9104-S(S)

Single Line SIP Emergency
Speaker Phone



VS-9104-S-A(S)



VS-9104-S-B(S)-EW

- Single line SIP emergency phone
- Full duplex Wall-mount speakerphone
- Faceplate with customizable hotel logo
- Optional emergency wire (white color only)

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At AEi your satisfaction is our priority.



1. Features

Keys	<ul style="list-style-type: none"> • Dial keys (0~9, *, #) • Function keys 4 or 5 emergency keys
Phone Features	<ul style="list-style-type: none"> • Up to 4 or 5 programmable emergency keys • Full duplex speaker phone
Easy Administration	<ul style="list-style-type: none"> • Web GUI • Auto provisioning • Firmware upgrade via web
Codec	<ul style="list-style-type: none"> • G.711 (a-law, μ-law)
Network Protocol	<ul style="list-style-type: none"> • Static IP, DHCP Client • HTTP server • ToS / VLAN IEEE 802.1 p/q
SIP	<ul style="list-style-type: none"> • SIP V2 (RFC3261)
Security	<ul style="list-style-type: none"> • Web login authentication for web setup • MD5 for SIP authentication (RFC2069/ RFC2617) • TLS 1.2
DTMF	<ul style="list-style-type: none"> • In-Band / Out-of-Band DTMF(RFC2833) / SIP Info (RFC2976)
Voice Quality	<ul style="list-style-type: none"> • CNG: Comfortable noise generator • Jitter buffer/PLC • Echo canceller: LEC / AEC
Tones	<ul style="list-style-type: none"> • Ring back tone (local), Busy tone, Dial tone

2. Hardware Specifications

Power	<ul style="list-style-type: none"> • PoE: IEEE 802.3af compliant • AC adaptor: Input: 100 ~ 240 VAC, Output: 5V / 3A (optional)
Ethernet Cable	<ul style="list-style-type: none"> • 0.5 feet x 1
Jacks	<ul style="list-style-type: none"> • 10/100 RJ45 LAN port x 1
Emergency wire	<ul style="list-style-type: none"> • 3.3 feet x 1 (white color only)
Size and Weight	<ul style="list-style-type: none"> • Dimensions: 180mm(L) x100mm(W) x 28.5mm(H), Weight: 230g

3. Regulatory

	USA	EU
EMI	FCC Part 15B	EN 55032
Safety		EN 62368-1
EMC		EN 55035
RoHS	Comply with directive 2011/65/EU	
Temperature	<ul style="list-style-type: none"> • Storage: Low temperature at -10°C • Operating: Low temperature at +5°C 	<ul style="list-style-type: none"> High temperature at +60°C High temperature at +35°C

Model:

- VS-9104-S-A(S)
- VS-9104-S-A(S)-EW
- VS-9104-S-B(S)
- VS-9104-S-B(S)-EW

