

VS-9104-S(S)

VS-9104-S(S)-EW

Single Line
SIP Speaker Phone



VS-9104-S-A(S)



VS-9104-S-B(S)

- Single line SIP phone.
- Wall mount speaker phone.
- Full duplex speakerphone.
- Customizable service dials.
- Message key with indicator.
- Faceplate with customizable hotel logo.
- Optional emergency wire.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



1. Features

Keys	<ul style="list-style-type: none"> Dial keys (0~9, *, #) Function keys SPEAKER, MUTE, VOLUME, 4 Service dial keys
Phone Features	<ul style="list-style-type: none"> Mute and unmute Three level speaker and ringer volume control 4 or 5 programmable service dials Full duplex speaker phone
Easy Administration	<ul style="list-style-type: none"> Web GUI Auto provisioning Firmware upgrade via web
Codec	<ul style="list-style-type: none"> G.711 (a-law, μ-law)
Network Protocol	<ul style="list-style-type: none"> Static IP, DHCP Client HTTP server ToS / VLAN IEEE 802.1 p/q
SIP	<ul style="list-style-type: none"> SIP V2 (RFC3261)
Security	<ul style="list-style-type: none"> Web login authentication for web setup TLS 1.2 MD5 for SIP authentication (RFC2069/ RFC2617)
DTMF	<ul style="list-style-type: none"> In-Band / Out-of-Band DTMF(RFC2833) / SIP Info (RFC2976)
Voice Quality	<ul style="list-style-type: none"> CNG: Comfortable noise generator Jitter buffer/PLC Echo canceller: LEC / AEC
Tones	<ul style="list-style-type: none"> Ring back tone (local), Busy tone, Dial tone

2. Hardware Specifications

LED Indications	<ul style="list-style-type: none"> MUTE(red), SPEAKER(red), MESSAGE(red) keys
Power	<ul style="list-style-type: none"> PoE : IEEE 802.3af compliant AC adaptor: Input: 100 ~ 240 VAC, Output: 5V / 1.5A (optional)
Ethernet Cable	<ul style="list-style-type: none"> 0.5 feet x 1
Jacks	<ul style="list-style-type: none"> 10/100 RJ45 LAN port x 1
Emergency wire	<ul style="list-style-type: none"> 3.3 feet x 1 (VS-9104(S)-EW only)
Size and Weight	<ul style="list-style-type: none"> Dimensions: 180mm(L) x100mm(W) x 28.5mm(H), Weight: 230g

3. Regulatory

	USA	EU	
EMI	FCC Part 15B	EN55032	
Safety		EN60950-1	
EMC		EN55024	
		EN61000-3-2	EC61000-4-4
		EN61000-3-3	EC61000-4-5
		IEC61000-4-2	EC61000-4-6
		IEC61000-4-3	EC61000-4-8
RoHS	<ul style="list-style-type: none"> Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC) 		
Temperature	<ul style="list-style-type: none"> Storage: Low temperature at -10°C Operating Low temperature at +5°C 	<ul style="list-style-type: none"> High temperature at +60°C High temperature at +35°C 	

Model:

- VS-9104-S(S)
- VS-9104-S(S)-EW
- VS-9104-S-A(S)
- VS-9104-S-B(S)
- VS-9104-S-TI(S)
- VS-9104-S-TI(S)-EW
- VS-9104-S-ATI(S)
- VS-9104-S-BTI(S)

