

VS-9104-S(S) -EW

Single Line
SIP Speaker Phone



- Single line SIP phone.
- Wall mountable speaker phone.
- Full duplex speakerphone.
- Customizable service dials.
- Message key with indicator.
- Faceplate with customizable hotel logo.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



1. Features

Keys	<ul style="list-style-type: none"> Dial keys (0~9, *, #) Function keys SPEAKER, MUTE, VOLUME, 4 Service dial keys, 	
Phone Features	<ul style="list-style-type: none"> Mute and Resume Three level speaker and ringer volume control Emergency wire with button 	<ul style="list-style-type: none"> 4 or 5 programmable service dials Full duplex speaker phone
Easy Administration	<ul style="list-style-type: none"> Web GUI Auto provisioning 	<ul style="list-style-type: none"> Firmware upgrade via web
Codec	<ul style="list-style-type: none"> G.711 (a-law, μ-law) 	
Network Protocol	<ul style="list-style-type: none"> Static IP, DHCP Client HTTP server 	<ul style="list-style-type: none"> ToS / VLAN IEEE 802.1 p/q STUN (RFC 3489)
SIP	<ul style="list-style-type: none"> SIP V2 (RFC3261) 	
Security	<ul style="list-style-type: none"> Web login authentication for web setup TLS 1.2 In-Band / Out-of-Band DTMF(RFC2833) / SIP Info (RFC2976) 	<ul style="list-style-type: none"> MD5 for SIP authentication (RFC2069/ RFC2617)
DTMF	<ul style="list-style-type: none"> Jitter buffer/PLC 	
Voice Quality	<ul style="list-style-type: none"> Ring back tone (local), Busy tone, Dial tone 	
Tones		

2. Hardware Specifications

LED Indications	<ul style="list-style-type: none"> MUTE(red), SPEAKER(red), MESSAGE(red) keys
Power	<ul style="list-style-type: none"> PoE : IEEE 802.3af AC adaptor: Input: 100 ~ 240 VAC, Output: 5V / 1.5A (optional)
Jacks	<ul style="list-style-type: none"> 10/100 RJ45 LAN port x 1, RJ11 jack x 1
Ethernet Cable	<ul style="list-style-type: none"> 0.5 feet x 1
Emergency Wire	<ul style="list-style-type: none"> Emergency cord with button, 3.3 feet x 1
Size and Weight	<ul style="list-style-type: none"> Dimensions: 180mm(L) x100mm(W) x 28.5mm(H), Weight: 228g

3. Regulatory

	USA	EU	
EMI	FCC Part 15B	EN55032	
Safety		EN 60950-1	
EMC		EN55024	
		EN61000-3-2	EC61000-4-4
		EN61000-3-3	EC61000-4-5
		IEC61000-4-2	EC61000-4-6
		IEC61000-4-3	EC61000-4-8
RoHS	<ul style="list-style-type: none"> Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC) 		
Temperature	<ul style="list-style-type: none"> Storage: Low temperature at -10°C Operating Low temperature at 0°C 	<ul style="list-style-type: none"> High temperature at +60°C High temperature at +40°C 	

Model:

VS-9104-S(S)-EW

