

VS-9104-S(S) | Single Line  
SIP Speaker Phone



- Single line SIP phone.
- Wall mountable speaker phone.
- Full duplex speakerphone.
- Customizable service dials.
- Message key with indicator.
- Faceplate with customizable hotel logo.

**AEi** brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



## 1. Features

Keys	<ul style="list-style-type: none"> <li>Dial keys (0~9, *, #)</li> <li>Function keys SPEAKER, MUTE, VOLUME, 4 Service dial keys</li> </ul>	
Phone Features	<ul style="list-style-type: none"> <li>Mute and Resume</li> <li>Three level speaker and ringer volume control</li> </ul>	<ul style="list-style-type: none"> <li>4 programmable service dials</li> <li>Full duplex speaker phone</li> </ul>
Easy Administration	<ul style="list-style-type: none"> <li>Web GUI</li> <li>Auto provisioning</li> </ul>	<ul style="list-style-type: none"> <li>Firmware upgrade via web</li> </ul>
Codec	<ul style="list-style-type: none"> <li>G.711 (a-law, <math>\mu</math>-law)</li> </ul>	
Network Protocol	<ul style="list-style-type: none"> <li>Static IP, DHCP Client</li> <li>HTTP server</li> </ul>	<ul style="list-style-type: none"> <li>ToS / VLAN IEEE 802.1 p/q</li> <li>STUN (RFC 3489)</li> </ul>
SIP	<ul style="list-style-type: none"> <li>SIP V2 (RFC3261)</li> </ul>	
Security	<ul style="list-style-type: none"> <li>Web login authentication for web setup</li> <li>TLS 1.2</li> </ul>	<ul style="list-style-type: none"> <li>MD5 for SIP authentication (RFC2069/RFC2617)</li> </ul>
DTMF	<ul style="list-style-type: none"> <li>In-Band / Out-of-Band DTMF(RFC2833) / SIP Info (RFC2976)</li> </ul>	
Voice Quality	<ul style="list-style-type: none"> <li>Jitter buffer/PLC</li> </ul>	
Tones	<ul style="list-style-type: none"> <li>Ring back tone (local), Busy tone, Dial tone</li> </ul>	

## 2. Hardware Specifications

LED Indications	<ul style="list-style-type: none"> <li>MUTE(red), SPEAKER(red), MESSAGE(red) keys</li> </ul>
Power	<ul style="list-style-type: none"> <li>PoE : IEEE 802.3af</li> <li>AC adaptor: Input: 100 ~ 240 VAC, Output: 5V / 1.5A (optional)</li> </ul>
Jacks	<ul style="list-style-type: none"> <li>10/100 RJ45 LAN port x 1</li> </ul>
Ethernet cable	<ul style="list-style-type: none"> <li>0.5 feet x 1</li> </ul>
Size and Weight	<ul style="list-style-type: none"> <li>Dimensions: 180mm(L) x100mm(W) x 28.5mm(H), Weight: 228g</li> </ul>

## 3. Regulatory

	USA	EU	
EMI	FCC Part 15B	EN55032	
Safety		EN 60950-1	
EMC		EN55024	EC61000-4-4
		EN61000-3-2	EC61000-4-5
		EN61000-3-3	EC61000-4-6
		IEC61000-4-2	EC61000-4-8
		IEC61000-4-3	EC61000-4-11
RoHS	<ul style="list-style-type: none"> <li>Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)</li> </ul>		
Temperature	<ul style="list-style-type: none"> <li>Storage: Low temperature at -10°C</li> <li>Operating Low temperature at 0°C</li> </ul>	<ul style="list-style-type: none"> <li>High temperature at +60°C</li> <li>High temperature at +40°C</li> </ul>	

**Model:**

**VS-9104-S(S)**

