

Serving the Hospitality Industry with Advanced IP and Analog Telephony Solutions Worldwide

AGR-6106-S AGR-6109-S

Single line Analog phone





- Single line analog phone.
- Hearing aid support
- Full duplex speakerphone.
- Message waiting indicator.
- 6 or 9 customizable service dials.
- Faceplate with customizable hotel logo.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality,impeccable workmanship and stylish products.

At AEi your satisfaction is our priority.





AEi- Corporate Office

Millbrae, California U.S.A Sales: +1.650.552.9416 sales@aeicommunications.com

AEi- CALA Office

Lima, Peru Sales : +51.9.8257.6251 cala@aeicommunications.com

AEi- Asia Pacific Office

New Taipei City, Taiwan Sales: +886.2.2696.8809 asiapac@aeicommunications.com

AEi- EMEA Office

London, United Kingdom Sales : +44 (0)1753.643736 emea@aeicommunications.com

AEi- Southern Asia Office

Penang, Malaysia Sales:+604.3994341 so.asia@aeicommunications.com

AEi- CEE&CIS Office

Budva, Montenegro Sales: +382 69 891 251 eastern.europe@aeicommunications.com

1. Features

Keys • Dial keys (0~9, *, #)
• Line keys N/A

• Function keys Speaker, Volume up/down, 6 or 9 programmable service keys

Phone Features • Single line telephone system with speakerphone

Adjustable High-low ringer (2 way selectable switch)

8 steps speakerphone digital volume control

• 4 steps handset digital volume control

6 non volatile one-touch programmable speed dial memory button

Tone dialing only

• Hearing Aid Receiver Compliant

PBX / Standard Line compatible

Multi Purpose LED indicator for Message Waiting and Incoming Ring

2. Hardware Specifications

Power • Line Power (without AC adaptor or battery)

Jacks • RJ11 PSTN jack x 1

Size and Weight

Dimensions: 191mm(L) x 110mm(W) x 106mm(H), Weight: 576g

3. Regulatory USA EU

PSTN Part 68 TBR 21

EMI FCC Part 15B EN55032 & EN55024

RoHS • Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)

Temperature • Storage: Low temperature at -10°C High temperature at +60°C

Operating Low temperature at 0°C High temperature at +40°C

Model:

AGR-6106-S

AGR-6109-S





