

AMT-6110-S

1 or 2 Lines  
Analog Phone

AMT-6210-S



- 1 or 2 lines analog phone.
- Full duplex speakerphone.
- 10 customizable service dials.
- Message waiting indicator.
- Faceplate with customizable hotel logo.

**AEI** brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEI** your satisfaction is our priority.



## 1. Features

| Keys           | 6210   | 6110   |
|----------------|--|--|
|                | <ul style="list-style-type: none"> <li>Dial keys (0~9, *, #)</li> <li>Line keys Line1, Line2 with red/green color LED</li> <li>Function keys Conference, Hold, Redial, Mute, Speaker, Message, Volume up/down, 10 Service dial keys</li> </ul>         | <ul style="list-style-type: none"> <li>(0~9, *, #)</li> <li>NA</li> <li>Flash, Redial, Mute, Speaker, Message, Volume up/down, 10 Service dial keys</li> </ul>   |
| Phone Features | <ul style="list-style-type: none"> <li>One or Two Lines</li> <li>3-Way Conference(6210 only)</li> <li>Call Hold and resume(6210 only)</li> <li>Mute and Resume</li> <li>Red color message waiting indicator for ringing and message waiting</li> </ul> | <ul style="list-style-type: none"> <li>10 programmable service dials</li> <li>Selectable flash timing(6110 only)</li> <li>Handset, Speaker volume control</li> <li>Ringer volume switch</li> <li>Redial last call</li> </ul> |

## 2. Hardware Specifications

|                 |  |
|-----------------|--|
| LED Indications | <ul style="list-style-type: none"> <li>Line keys, Conf, Mute, Speaker keys, and Message waiting indicator</li> </ul> |
| Power           | <ul style="list-style-type: none"> <li>Telephone line powered</li> </ul>   |
| Jacks           | <ul style="list-style-type: none"> <li>RJ11 PSTN jack x 2, RJ9 Handset jack x1,</li> </ul>                           |
| Ring Voltage    | <ul style="list-style-type: none"> <li>40V RMS minimum</li> </ul>  |
| Line cord       | <ul style="list-style-type: none"> <li>10 feet x 1</li> </ul>  |
| Size and Weight | <ul style="list-style-type: none"> <li>Dimensions:227mm(L) x158mm(W) x 141mm(H), Weight: 835g</li> </ul>             |

## 3. Regulatory

|             | USA   | EU   |
|-------------|---|--|
| PSTN        | Part 68   | TBR 21   |
| EMC         | FCC Part 15B  | EN55032 & EN55024  |
| RoHS        | <ul style="list-style-type: none"> <li>Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)</li> </ul> |  |
| Temperature | <ul style="list-style-type: none"> <li>Storage: Low temperature at -10°C</li> <li>Operating Low temperature at 0°C</li> </ul>           | <ul style="list-style-type: none"> <li>High temperature at +60°C</li> <li>High temperature at +40°C</li> </ul> |

**Model:**

**AMT-6110-S**

**AMT-6210-S**

