

AMT-9110-SM

AMT-9210-SM

1 or 2 Lines
Corded
Analog Phone



- 1 or 2 lines corded analog phone.
- Full duplex speakerphone.
- Pair up to 4 cordless remotes.
- 10 customizable service dials.
- Message waiting indicator.
- Customizable hotel logo and service dials.

AEI brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEI** your satisfaction is our priority.



AEi- Corporate Office

Millbrae, California U.S.A
Sales : +1.650.552.9416
sales@aeicomcommunications.com

AEi- CALA Office

Lima, Peru
Sales : +51.9.8257.6251
cala@aeicomcommunications.com

AEi- Asia Pacific Office

New Taipei City, Taiwan
Sales : +886.2.2696.8809
asiapac@aeicomcommunications.com

AEi- EMEA Office

London, United Kingdom
Sales : +44 (0)1753.643736
emea@aeicomcommunications.com

AEi- Southern Asia Office

Penang, Malaysia
Sales : +604.3994341
so.asia@aeicomcommunications.com

AEi- CEE&CIS Office

Budva, Montenegro
Sales : +382 69 891 251
eastern.europe@aeicomcommunications.com

1. Features

	Keys	9210	9110
	<ul style="list-style-type: none"> Dial keys Line keys Function keys 	(0~9, *, #) Line1, Line2 with red/green color LED Conference, Hold, Redial, Mute, Speaker, Message, Volume up/down, 10 Service dial keys	(0~9, *, #) N/A Flash, Redial, Mute, Speaker, Message, Volume up/down, 10 Service dial keys
Phone Features	<ul style="list-style-type: none"> One or Two Lines Message key with message waiting indicator 3-Way Conference(9210 only) Call Hold and resume Mute and Resume 		<ul style="list-style-type: none"> 10 programmable service dials Selectable flash timing (9110 only) Speaker and ringer volume control Redial last call Red color message waiting indicator for ringing and message waiting
DECT Standard	<ul style="list-style-type: none"> DECT / CAT iq2.0 compatible Radio Frequency Range : 1880~1930 MHz EU : 1881.792(ch0)~1897.344(ch9)10Channels US : 1921.536(ch0)~1928.448(ch4) 5 Channels JP : 1895.616(ch0)~1902.528(ch4) 5 Channels 		<ul style="list-style-type: none"> Channel Space : 1728 KHz Bit rate : 1150 Kbit/s Modulation : GFSK Voice coding : 16 Kbit/s RF power : 17 dBm

2. Hardware Specifications

LED Indications	<ul style="list-style-type: none"> Line keys, Conf/Hold, Mute, Speaker keys, and Message waiting indicator
Power	<ul style="list-style-type: none"> AC adaptor: Input: 100 ~ 240 VAC, Output: 5.9 V / 1A
Jacks	<ul style="list-style-type: none"> RJ14 PSTN jack x 1, DC jack x 1, RJ9 Handset jack x 1
Ethernet cable	<ul style="list-style-type: none"> 10 feet x 1
Size and Weight	<ul style="list-style-type: none"> Dimensions:227mm(L) x158mm(W) x 142mm(H) , Weight: 950g

3. Regulatory

	USA	EU
RF	FCC Part 15D	EN 301406
EMI	FCC Part 15B	EN 300386
SAR		EN 62479
Safety		EN 60950-1
EMC		EN 301489-1/6
PSTN	Part 68	TBR 21
RoHS	<ul style="list-style-type: none"> Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC) 	
Temperature	<ul style="list-style-type: none"> Storage: Low temperature at -10°C Operating Low temperature at 0°C 	<ul style="list-style-type: none"> High temperature at +60°C High temperature at +40°C

Model:

AMT-9110-SM

AMT-9210-SM

AMT-9110-SM-79

AMT-9210-SM-79

