

# Serving the Hospitality Industry with Advanced IP and Analog Telephony Solutions Worldwide

GR-8106-SPB

GR-8206-SPB

1 or 2 Lines Cordless Handset phone





- 1 or 2 lines cordless handset.
- Full duplex speakerphone.
- Message waiting indicator.
- Customizable hotel logo and service dials.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality,impeccable workmanship and stylish products.

At AEi your satisfaction is our priority.





# **AEi- Corporate Office**

Millbrae, Ca<mark>l</mark>ifornia U.S.A Sales : +1.650.552.9416 sales@aeicommunications.com

## AEi- CALA Office

Lima, Peru Sales : +51.9.8257.6251 cala@aeicommunications.com

## AEi- Asia Pacific Office

New Taipei City, Taiwan Sales: +886.2.2696.8809 asiapac@aeicommunications.com

#### AEi- EMEA Office

London, United Kingdom Sales : +44 (0)1753.643736 emea@aeicommunications.com

# AEi- Southern Asia Office

Penang, Malaysia Sales:+604.3994341 so.asia@aeicommunications.com

#### AEi- CEE&CIS Office

RF power: 7 dBm

Standby Time: 240 hrs

Talking Time: 9 hrs

Budva, Montenegro Sales: +382 69 891 251 eastern.europe@aeicommunications.com

# 1. Features

Handset
---------

Keys 8206 8106 (0~9, \*, #)Dial keys (0~9, \*, #) Line keys Line1, Line2, END Line, END Function keys Hold, Speaker, Volume, 6 Service Mute, Speaker, Volume, 6 Service dial keys dial keys Phone Features One or Two Lines 6 programmable service dials Call Hold and resume(8206 only) Mute and resume(8106 only) Handset, Speaker, and Ringer volume control Red color message waiting indicator Full duplex speaker phone for ringing and message waiting Display Contents Main logo **DECT** signal status Service dial icons Line status Battery status: power level, charging status Firmware Version **DECT Standard** DECT / CAT iq2.0 compatible Channel Space: 1728 KHz Radio Frequency Range: 1880~1930 MHz Bit rate: 1150 Kbit/s EU: 1881.792(ch0)~1897.344(ch9) 10 Channels Modulation: GFSK US: 1921.536(ch0)~1928.448(ch4) 5 Channels Voice coding: 16 Kbit/s

# 2. Hardware Specifications

## **Handset**

Display • 1.8" TFT color display

LED Indications 

 Message waiting indicator and keypad backlight

Power • 3.7v / 900 mAh Li-ion battery

• Charging Time : 5 hrs

Contact pins • 3 contact pins for charging and hook detecting

Size and Weight • Dimensions: 175mm(L) x 50mm(W) x 24mm(H), Weight: 180g(battery included)

JP: 1895.616(ch0)~1902.528(ch4) 5 Channels

# **Stand Cradle**

LED Indications

Handset charging indicators

Power • AC adaptor: Input: 100 ~ 240 VAC, Output: 5.9V / 1A

Jacks • DC jack x 1

Contact pins • 3 contact pins for charging and hook detecting

Size and Weight • Dimensions:106mm(L) x88mm(W) x 97mm(H), Weight: 290g

Dimensions:106mm(L) x88mm(W) x 179mm(H), Weight: 455g (handset included)

 Regulatory
 USA
 EU

 RF
 FCC Part 15D
 EN 301406

 EMI
 FCC Part 15B
 EN 300386

 SAR
 EN 62479

 Safety
 EN 60950-1

 EMC
 EN 301489-1/6

RoHS

• Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)

Temperature

• Storage: Low temperature at -10°C High temperature at +60°C

Operating Low temperature at +00°C
 High temperature at +40°C

Model:

GR-8106-SPB

GR-8206-SPB



