

GR-8106-SPC

GR-8206-SPC

1 or 2 Lines  
Cordless  
Handset phone



- 1 or 2 lines cordless handset.
- Full duplex speakerphone.
- Message waiting indicator.
- Customizable hotel logo and service dials.

**AEi** brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



## 1. Features

### Handset

Keys	8206	8106
	<ul style="list-style-type: none"> <li>Dial keys (0~9, *, #)</li> <li>Line keys Line1, Line2, END</li> <li>Function keys Hold, Speaker, Volume, 6 Service dial keys</li> </ul>	<ul style="list-style-type: none"> <li>(0~9, *, #)</li> <li>Line, END</li> <li>Mute, Speaker, Volume, 6 Service dial keys</li> </ul>
Phone Features	<ul style="list-style-type: none"> <li>One or Two Lines</li> <li>Call Hold and resume(8206 only)</li> <li>Handset, Speaker, and Ringer volume control</li> <li>Full duplex speaker phone</li> </ul>	<ul style="list-style-type: none"> <li>6 programmable service dials</li> <li>Mute and resume(8106 only)</li> <li>Red color message waiting indicator for ringing and message waiting</li> </ul>
Display Contents	<ul style="list-style-type: none"> <li>Main logo</li> <li>Service dial icons</li> <li>Battery status: power level, charging status</li> </ul>	<ul style="list-style-type: none"> <li>DECT signal status</li> <li>Line status</li> <li>Firmware Version</li> </ul>
DECT Standard	<ul style="list-style-type: none"> <li>DECT / CAT iq2.0 compatible</li> <li>Radio Frequency Range : 1880~1930 MHz</li> <li>EU : 1881.792(ch0)~1897.344(ch9) 10 Channels</li> <li>US : 1921.536(ch0)~1928.448(ch4) 5 Channels</li> <li>JP : 1895.616(ch0)~1902.528(ch4) 5 Channels</li> </ul>	<ul style="list-style-type: none"> <li>Channel Space : 1728 KHz</li> <li>Bit rate : 1150 Kbit/s</li> <li>Modulation : GFSK</li> <li>Voice coding : 16 Kbit/s</li> <li>RF power : 7 dBm</li> </ul>

## 2. Hardware Specifications

### Handset

Display	<ul style="list-style-type: none"> <li>1.8" TFT color display</li> </ul>	
LED Indications	<ul style="list-style-type: none"> <li>Message waiting indicator and keypad backlight</li> </ul>	
Power	<ul style="list-style-type: none"> <li>3.7v / 900 mAh Li-ion battery</li> <li>Charging Time : 5 hrs</li> </ul>	<ul style="list-style-type: none"> <li>Standby Time : 240 hrs</li> <li>Talking Time: 9 hrs</li> </ul>
Contact pins	<ul style="list-style-type: none"> <li>3 contact pins for charging and hook detecting</li> </ul>	
Size and Weight	<ul style="list-style-type: none"> <li>Dimensions: 175mm(L) x 50mm(W) x 24mm(H), Weight: 180g(battery included)</li> </ul>	

### Flat Cradle

LED Indications	<ul style="list-style-type: none"> <li>Handset charging indicators</li> </ul>
Power	<ul style="list-style-type: none"> <li>AC adaptor: Input: 100 ~ 240 VAC, Output: 5.9V / 1A</li> </ul>
Jacks	<ul style="list-style-type: none"> <li>DC jack x 1</li> </ul>
Contact pins	<ul style="list-style-type: none"> <li>2 contact pins for charging</li> </ul>
Size and Weight	<ul style="list-style-type: none"> <li>Dimensions:193mm(L) x109mm(W) x 102mm(H), Weight: 350g</li> <li>Dimensions:193mm(L) x109mm(W) x 111mm(H), Weight: 530g (handset included)</li> </ul>

## 3. Regulatory

	USA	EU
RF	FCC Part 15D	EN 301406
EMI	FCC Part 15B	EN 300386
SAR		EN 62479
Safety		EN 60950-1
EMC		EN 301489-1/6
RoHS	<ul style="list-style-type: none"> <li>Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)</li> </ul>	
Temperature	<ul style="list-style-type: none"> <li>Storage: Low temperature at -10°C</li> <li>Operating Low temperature at 0°C</li> </ul>	<ul style="list-style-type: none"> <li>High temperature at +60°C</li> <li>High temperature at +40°C</li> </ul>

### Model:

**GR-8106-SPC**

**GR-8206-SPC**

