

MP-7102(S)

Single Line
SIP Phone



- Single line SIP phone.
- 2 customizable service dials.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



1. Features

Keys	<ul style="list-style-type: none"> Dial keys (0~9, *, #) Function keys M1, M2 service dial keys
Phone Features	<ul style="list-style-type: none"> Two levels receiver volume(NORMAL/HIGH) Two pre-set service dials
Easy Administration	<ul style="list-style-type: none"> Web GUI Auto provisioning via TFTP Firmware upgrade via TFTP
Codec	<ul style="list-style-type: none"> G.711 (a-law, μ-law)
Network Protocol	<ul style="list-style-type: none"> Static IP, DHCP Client HTTP server ToS / VLAN IEEE 802.1 p/q STUN (RFC 3489)
SIP	<ul style="list-style-type: none"> SIP V2 (RFC3261)
Security	<ul style="list-style-type: none"> Web login authentication for web setup TLS 1.2 MD5 for SIP authentication (RFC2069/ RFC2617)
DTMF	<ul style="list-style-type: none"> In-Band / Out-of-Band DTMF(RFC2833) / SIP Info (RFC2976)
Voice Quality	<ul style="list-style-type: none"> Jitter buffer
Tones	<ul style="list-style-type: none"> Ring back tone (local), Busy tone, Dial tone

2. Hardware Specifications

Power	<ul style="list-style-type: none"> PoE : IEEE 802.3af; Non-isolated
Jacks	<ul style="list-style-type: none"> RJ45 10/100Mbs: LAN port x 1, RJ9 Handset jack x 1
Ethernet cable	<ul style="list-style-type: none"> 9 feet x 1
Size and Weight	<ul style="list-style-type: none"> Dimensions: 214mm(L) x 142mm(W) x 125mm(H), Weight: 700g

3. Regulatory

	USA	EU
EMI	FCC Part 15B	EN55032
Safety		EN 60950-1
EMC		EN55024 IEC 61000-4-4
		EN61000-3-2 IEC 61000-4-5
		EN61000-3-3 IEC 61000-4-6
		IEC61000-4-2 IEC 61000-4-8
		IEC61000-4-3 IEC 61000-4-11
RoHS	<ul style="list-style-type: none"> Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC) 	
Temperature	<ul style="list-style-type: none"> Storage: Low temperature at -10°C Operating Low temperature at 0°C 	<ul style="list-style-type: none"> High temperature at +60°C High temperature at +40°C

Model:
MP-7102(S)

