



VM-8108-SMKU(PoE)

1 or 2 Lines
 Cordless SIP
 Phone

VM-8208-SMKU(PoE)



- 1 or 2 lines cordless phone.
- Magnetic hook switch.
- Full duplex speakerphone.
- 8 customizable service dials.
- Pair up to 4 cordless remotes.
- Message waiting key with indicator.
- Faceplate with customizable hotel logo.



AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At AEi your satisfaction is our priority.



1. Features

Handset

	8208	8108
Keys	<ul style="list-style-type: none"> Dial keys (0~9, *, #) Line keys Line1, Line2, END Function keys SPEAKER, VOLUME +/-, HOLD, MESSAGE, FRONT DESK, EMERGENCY, and 3 soft keys 	<ul style="list-style-type: none"> (0~9, *, #) Line, END SPEAKER, VOLUME +/-, MUTE, MESSAGE, FRONT DESK, EMERGENCY, and 3 soft keys
Phone Features	<ul style="list-style-type: none"> One or Two Lines 3 hard key and 7 scrollable service dials Call Hold and resume(8208 only) Handset, Speaker, and Ringer volume control 	<ul style="list-style-type: none"> Full duplex speaker phone Mute and resume(8108 only) Red color message waiting indicator for ringing and message waiting
Display Contents	<ul style="list-style-type: none"> Main logo Service dial list/icons Battery status: power level, charging status 	<ul style="list-style-type: none"> DECT signal status Line status Firmware Version
DECT Standard	<ul style="list-style-type: none"> DECT / CAT iq2.0 compatible Radio frequency range : 1880~1930 MHz EU: 1881.792(ch0)~1897.344(ch9) 10 channels US: 1921.536(ch0)~1928.448(ch4) 5 channels JP: 1895.616(ch0)~1902.528(ch4) 5 Channels 	<ul style="list-style-type: none"> Channel space : 1728 KHz Bit rate : 1150 Kbit/s Modulation : GFSK Voice coding : 16 Kbit/s RF power : 7 dBm

Base		8208	8108
Keys		(0~9, *, #)	(0~9, *, #)
		Line1, Line2 with red color LED	N/A
		REDIAL, SPEKAER, VOLUME +/-, HOLD, MESSAGE, 8 Service dial keys	REDIAL, SPEKAER, VOLUME +/-, MUTE, MESSAGE, 8 Service dial keys
Phone Features		8 customizable service dials	Mute and resume(8108 only)
		Call Hold and resume(8208 only)	Red color message key with indicator
		Handset, speaker and ringer volume control	Ringing indicator
		Redial last call	Full duplex speaker phone
Display Contents		Talking time	SIP Register Status
		IP Address	Firmware Version
		MAC Address	Failed Network link Warning
Easy Administration		Web GUI	Firmware upgrade via TFTP
		Auto provisioning via TFTP	
Codec		G.711	
Network Protocol		HTTP server	
		ToS / VLAN IEEE 802.1 p/q	
SIP		SIP V2 (RFC3261)	
Security		Web login authentication for web setup	
		MD5 for SIP authentication (RFC 2069/ RFC2617)	
		TLS 1.2	
DTMF		In-Band / Out-of-Band DTMF(RFC2833) / SIP Info (RFC2976)	
Voice Quality		Echo canceller: LEC / AEC	Jitter buffer/PLC
		CNG: Comfortable noise generator	
Tones		Ring back tone (local), Busy tone, Dial tone	
DECT Standard		DECT / CAT iq2.0 compatible	Channel Space : 1728 KHz
		Radio Frequency Range : 1880~1930 MHz	Bit rate : 1150 Kbit/s
		EU : 1881.792(ch0)~1897.344(ch9) 10 Channels	Modulation : GFSK
		US : 1921.536(ch0)~1928.448(ch4) 5 Channels	Voice coding : 16 Kbit/s
		JP : 1895.616(ch0)~1902.528(ch4) 5 Channels	RF power : 17 dBm

2. Hardware Specifications

Handset

Display	• 2.0" TFT color display	
LED Indications	• Message waiting indicator and keypad backlight	
Power	• 3.7v / 900 mAh Li-ion battery	• Standby Time : 240 hrs
	• Charging Time : 5 hrs	• Talking Time: 9 hrs
Contact pins	• 3 contact pins for charging, hook detecting and auto-pairing	
Size and Weight	• Dimensions: 190mm(L) x 50mm(W) x 16.5mm mm(H), Weight: 140g(battery included)	

Base

Display	• Dot matrix LCM 16 x 2 with backlight
LED Indications	• Line keys(red), HOLD(red)/MUTE(red), SPEAKER(red), and MESSAGE(red) keys
Power	• PoE : IEEE 802.3af
Jacks	• RJ45 10/100 Mbs: LAN port x 1, PC port x1; DC jack x 1(for stand)
Contact pins	• 3 contact pins for charging and hook detecting.
Ethernet cable	• 9 feet x 1
Size and Weight	• Dimensions: 201mm(L) x132mm(W) x 121mm(H), Weight: 592g (Low profile)
	• Dimensions: 201mm(L) x132mm(W) x 156mm(H), Weight: 600g (High profile)

Stand

power	• USB output: DC 5V / 0.9A (MAX)
Jacks	• USB type A x 2

3. Regulatory

	USA	EU
RF	FCC Part 15D	EN 301406
EMI	FCC Part 15B	EN 300386
SAR		EN 62479
Safety		EN 60950-1
EMC		EN 301489-1/6
RoHS	• Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)	
Temperature	• Storage: Low temperature at -10°C	High temperature at +60°C
	• Operating Low temperature at 0°C	High temperature at +40°C

Model:

VM-8108-SMKU(PoE)

VM-8208-SMKU(PoE)

VM-8108-SMKU-9979(PoE)

VM-8208-SMKU-9979(PoE)

