

RW-5102(A)

Single Line
Analog phone



- Basic single-line corded analog phone
- Faceplate with customizable hotel logo
- 2 non volatile one-touch programmable speed dial buttons

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



1. Features

- | | |
|----------------|--|
| Keys | <ul style="list-style-type: none"> • Dial keys (0~9, *, #) • Function keys 2 speed dial keys |
| Phone Features | <ul style="list-style-type: none"> • Basic single line telephone system • Two levels receiver volume(NORMAL/HIGH) • Two levels ringer switch • 2 non volatile one-touch programmable speed dial buttons • Tone dialing only • Hearing aid receiver compliant PBX/ Standard line compatible |

2. Hardware Specifications

- | | |
|-----------------|---|
| Power | • Telephone line powered (without AC adaptor or battery) |
| Ring Voltage | • 40V RMS minimum |
| Jacks | • RJ11 PSTN jack x 1, RJ9 Handset jack x 1 |
| Line cord | • 0.7 feet x 1 |
| Size and Weight | • Dimensions:220mm(L) x150mm(W) x 120mm(H), Weight: 1160g |

3. Regulatory

	USA	EU
PSTN	Part 68	TBR 21
EMI	FCC Part 15B	EN55032 & EN55024 EN62368-1
RoHS	• Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)	
Telecom	• TIA/EIA 968-B compliant	
Temperature	• Storage: Low temperature at -10°C	High temperature at +60°C
	• Operating Low temperature at +5°C	High temperature at +35°C

Model:
RW-5102

