

Serving the Hospitality Industry with Advanced IP and Analog Telephony Solutions Worldwide

ASP-6110-S

Single Line Analog Phone



- Single line analog phone.
- Half duplex speakerphone.
- 10 customizable service dials.
- Message waiting key with indicator.
- Customizable hotel logo and service dials.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At AEi your satisfaction is our priority.





AEi- Corporate Office

Millbrae, California U.S.A Sales: +1.650.552.9416 sales@aeicommunications.com

AEi- CALA Office

Lima, Peru Sales : +51.9.8257.6251 cala@aeicommunications.com

AEi- Asia Pacific Office

New Taipei City, Taiwan Sales: +886.2.2696.8809 asiapac@aeicommunications.com

AEi- EMEA Office

London, United Kingdom Sales : +44 (0)1753.643736 emea@aeicommunications.com

AEi- Southern Asia Office

Penang, Malaysia Sales: +604.3994341 so.asia@aeicommunications.com

AEi- CEE&CIS Office

Budva, Montenegro Sales: +3826981251 eastern.europe@aeicommunications.com

1. Features

Keys. Dial keys (0~9, *, #)

> Function keys Speaker, Mute, Redial, Flash, Message and Volume up/down

10 Service dial keys Programmable Keys

Phone Features

- Mute and Resume
- 10 programmable services dials
- Programmable flash timing
- Red color message waiting indicator for ringing and message waiting
- Handset, Speaker volume control
- Ringer volume switch
- Redial last call

Hardware Specifications

RoHS

LED Indications

Power

Jacks

Ring Voltage

Line Cord

Size and Weight

- Speaker, Mute keys and Message waiting indicator
- Telephone line powered
- RJ11 PSTN jack x 2, RJ9 Handset jack x1,
- 40V RMS minimum
- 10 feet x 1
- Dimensions:227mm(L) x158mm(W) x 141mm(H), Weight: 835g

3. Regulatory USA EU **PSTN** Part 68 TBR 21

> **EMC** FCC Part 15B EN55032 & EN55024

Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC) Temperature Storage: Low temperature at -10 °C High temperature at +60 ℃

Operating: Low temperature at 0 °C High temperature at +40 ℃

Model:

ASP-6110-S





