

VM-6108-SF(A)

Single Line
Analog Phone



- Single line analog phone.
- Magnetic hook switch.
- Half duplex speakerphone.
- 8 customizable service dials.
- Message waiting key with indicator.
- Customizable hotel logo and service dials.
- Support FSK Message Waiting Signal Type.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



1. Features

| | |
|----------------|---|
| Keys | <ul style="list-style-type: none"> ● Dial keys (0~9, *, #) ● Function keys Speaker, Mute, Redial, Message and Volume up/down ● Programmable Keys 8 Service dial keys |
| Phone Features | <ul style="list-style-type: none"> ● Mute and Resume ● 8 programmable service dials ● Red color message waiting indicator for ringing and message waiting ● Handset, Speaker volume control ● Ringer volume switch ● Redial last call |

2. Hardware Specifications

| | |
|-----------------------------|---|
| LED Indications | <ul style="list-style-type: none"> ● Mute, Speaker keys, and Message waiting indicator |
| Power | <ul style="list-style-type: none"> ● Telephone line powered |
| Jacks | <ul style="list-style-type: none"> ● RJ11 PSTN jack x 1, RJ9 Handset jack x1, |
| Ring Voltage | <ul style="list-style-type: none"> ● 40V RMS minimum |
| Line Cord | <ul style="list-style-type: none"> ● 10 feet x 1 |
| Size and Weight | <ul style="list-style-type: none"> ● Dimensions: 201mm(L) x132mm(W) x 121mm(H), Weight: 620 g (Low profile) ● Dimensions: 201mm(L) x132mm(W) x 156mm(H), Weight: 620 g (High profile) |
| Message Waiting Signal Type | <ul style="list-style-type: none"> ● FSK, High Voltage, Low Voltage, Reverse Polarity |

3. Regulatory

| | USA | EU |
|-------------|---|--|
| PSTN | Part 68 | TBR 21 |
| EMC | FCC Part 15B | EN55032 & EN55024 |
| RoHS | <ul style="list-style-type: none"> ● Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC) | |
| Temperature | <ul style="list-style-type: none"> ● Storage: Low temperature at -10°C ● Operating: Low temperature at 0°C | <ul style="list-style-type: none"> High temperature at +60°C High temperature at +40°C |

Model:
VM-6108-SF(A)

