

VM-7108-S(S)

1 or 2 Lines  
SIP Phone

VM-7208-S(S)



- 1 or 2 lines corded SIP phone.
- Magnetic hook switch.
- Full duplex speakerphone.
- 8 customizable service dials.
- Message waiting key with indicator.
- Faceplate with customizable hotel logo.

**AEi** brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



## 1. Features

Keys	7208	7108
	<ul style="list-style-type: none"> <li>• Dial keys (0~9, *, #)</li> <li>• Line keys Line1, Line2 with red color LED</li> <li>• Function keys REDIAL, SPEKAER, VOLUME +/-, HOLD, MESSAGE, 8 Service dial keys</li> </ul>	<ul style="list-style-type: none"> <li>• (0~9, *, #)</li> <li>• NA</li> <li>• REDIAL, SPEKAER, VOLUME +/-, MUTE, MESSAGE, 8 Service dial keys</li> </ul>
Phone Features	<ul style="list-style-type: none"> <li>• 8 customizable service dials</li> <li>• Call Hold and resume(7208 only)</li> <li>• Handset, speaker and ringer volume control</li> <li>• Redial last call</li> </ul>	<ul style="list-style-type: none"> <li>• Mute and resume(7108 only)</li> <li>• Red color message key with indicator</li> <li>• Ringing indicator</li> <li>• Full duplex speaker phone</li> </ul>
Display Contents	<ul style="list-style-type: none"> <li>• Talking time</li> <li>• IP Address</li> <li>• MAC Address</li> <li>• Date and time</li> </ul>	<ul style="list-style-type: none"> <li>• SIP Register Status</li> <li>• Firmware Version</li> <li>• Failed Network link Warning</li> </ul>
Easy Administration	<ul style="list-style-type: none"> <li>• Web GUI</li> <li>• Auto provisioning via TFTP</li> </ul>	<ul style="list-style-type: none"> <li>• Firmware upgrade via TFTP</li> </ul>
Codec	<ul style="list-style-type: none"> <li>• G.711</li> </ul>	
Network Protocol	<ul style="list-style-type: none"> <li>• HTTP server</li> <li>• ToS / VLAN IEEE 802.1 p/q</li> </ul>	
SIP	<ul style="list-style-type: none"> <li>• SIP V2 (RFC3261)</li> </ul>	
Security	<ul style="list-style-type: none"> <li>• Web login authentication for web setup</li> <li>• MD5 for SIP authentication (RFC 2069/ RFC2617)</li> <li>• TLS 1.2</li> </ul>	
DTMF	<ul style="list-style-type: none"> <li>• In-Band / Out-of-Band DTMF(RFC2833) / SIP Info (RFC2976)</li> </ul>	
Voice Quality	<ul style="list-style-type: none"> <li>• CNG: Comfortable noise generator</li> <li>• Echo canceller: LEC / AEC</li> <li>• Jitter buffer/PLC</li> </ul>	
Tones	<ul style="list-style-type: none"> <li>• Ring back tone (local), Busy tone, Dial tone</li> </ul>	

## 2. Hardware Specifications

Display	• Dot matrix LCM 16 x 2 with backlight
LED Indications	• Line keys(red), HOLD(red)/MUTE(red), SPEAKER(red), and MESSAGE(red) keys
Power	• PoE : IEEE 802.3af • AC adaptor: Input: 100 ~ 240 VAC, Output: 5V / 1.5A (optional)
Jacks	• RJ45 10/100 Mbs: LAN port x 1, PC port x1; DC jack x 1, RJ9 Handset jack x 1
Ethernet cable	• 9 feet x 1
Size and Weight	• Dimensions: 201mm(L) x132mm(W) x 121mm(H), Weight: 620g (Low profile) • Dimensions: 201mm(L) x132mm(W) x 156mm(H), Weight: 625g (High profile)

## 3. Regulatory

	USA	EU	
EMI	FCC Part 15B	EN55032	
Safety		EN 60950-1	
EMC		EN55024	EC61000-4-4
		EN61000-3-2	EC61000-4-5
		EN61000-3-3	EC61000-4-6
		IEC61000-4-2	EC61000-4-8
		IEC61000-4-3	EC61000-4-11
RoHS	• Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)		
Temperature	• Storage: Low temperature at -10°C	High temperature at +60°C	
	• Operating Low temperature at 0°C	High temperature at +40°C	

**Model:**

**VM-7108-S(S)**

**VM-7208-S(S)**

